

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias	Description

<p>Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8577)</p> <p>-----</p> <p>Set post cor. to secs. 17, 18, 19 and 20, from which</p> <ul style="list-style-type: none"><li>A B.Oak 11" dia., bears N.71°E., 53 lks.</li><li>A B.Oak 12" dia., bears S.28°E., 43 lks.</li><li>A B.Oak 6" dia., bears S.59°W., 57 lks.</li><li>A B.Oak 12" dia., bears N.67°W., 67 lks.</li></ul>
<p>GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 20 Page(s) 8621)</p> <p>-----</p> <p>The Sec. cor., which having disappeared, I set a Pine post, 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 17, 18, 19 and 20, marked T32S S17 on NE.; R5W S20 on SE.; S19 on SW.; and S18 on NW. faces with 3 notches on S. and 5 notches on E. faces, and witnessed as described by the surveyor general.</p>
<p>George J. Wenderoth - June 1952 - M 8-25</p> <p>-----</p> <p>1/2" Iron pipe, from which</p> <ul style="list-style-type: none"><li>20" B.Oak bears N.67°W., 44.2 ft.</li><li>20" B.Oak bears S.59°W., 37.6 ft.</li><li>36" B.Oak bears S.40°E., 33.5 ft.</li><li>16" B.Oak bears N.21°30'W., 48.7 ft.</li></ul>
<p>Cor. OK, DCSO, John Powell, Aug. 1967</p>
<p>BLM Dependent resurvey by Arthur R. Rambo, &amp; Francis Simon Cadastral Surveyors under Group No. 2143, surveyed May 2006/Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21686-7)</p> <p>-----</p> <p>The cor. of secs. 17, 18, 19, and 20, perpetuated by Wenderoth, in 1952, monumented with an iron pipe, 1/2" dia., firmly set, projecting 6" above the ground, from which the remains of an original bearing tree:</p> <ul style="list-style-type: none"><li>A black oak, 22" dia., bears S.59°W., 37.6 ft., no marks visible on open and rotted face.</li></ul> <p>and a bearing tree mkd. by Wenderoth</p> <ul style="list-style-type: none"><li>A black oak, 32" dia., bears S.43°E., 33.8 ft., with illegible scribe marks visible on open blaze.</li></ul> <p>At the corner point</p> <p>Set a stainless steel post, 28" long, 2½" dia., 20" in the ground, directly over iron pipe, with brass cap (properly) mkd. continued next page</p>

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which new bearing trees

A fir, 9" dia. bears N.25°E. 13.6 ft. mkd. T32S R5W S17 BT

A fir, 7" dia. bears S.64°E. 34.3 ft. mkd. T32S R5W S20 BT

A fir, 17" dia., bears S.22¼°W., 9.4 ft., mkd. T32S R5W S19 BT.

A black oak, 12" dia., bears N.25°W., 24.5 ft., mkd. T32S R5W S18 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

Deposit a magnet in a white plastic case at the base of the stainless steel post.