

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 20 Page(s) 8588)

-----  
Set ¼ sec. post, from which  
A Fir 30" dia., bears N.35°W., 9 lks.  
A Cedar 72" dia., bears East, 17 lks.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - August 1967 - C.S. File 53/52-3

-----  
Found - Orig. 30" D.Fir now 36" stump, N.35°W., 5.7 ft., bark scribe visible.  
Orig. 72" now 74" Cedar, East, 11.2 ft., no scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office  
T 32 S R 5 W  
S 18 | S 17  
1967

New BT - 8" Cedar S.73½°W., 38.2 ft. mkd. ¼ S17 CS BT.

Reblazed and rescribed:

74" Cedar, East 11.2 ft. mkd. ¼ S17 CS BT.  
Corner lies in partially cut South of logging road, 300 ft

BLM Dependent resurvey by Arthur R. Rambo, & Francis Simon Cadastral Surveyors under Group No. 2143, surveyed May 2006/Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21690)

-----  
The ¼ sec. cor. of secs. 17 and 18, perpetuated by the Douglas County Surveyor's Office, in 1967, monumented with an iron post, 1¼" dia., firmly set, projecting 12" above the ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A sawed cedar stump, 74" dia., bears East, 11.2 ft., with scribe marks ¼ S17 CS BT visible on partially opened blaze (the visible marks were added by the Douglas County Surveyor's Office).

A sawed fir stump, 36" dia., bears N.35°W., 5.9 ft., no marks visible.

and a BT mkd. by the Douglas County Surveyor's Office

A sawed cedar stump, 18" dia., bears S. 71 ¼° W., 38.2 ft., with a healed blaze.

and new bearing trees

A fir, 10" dia., bears N.66¼°E., 9.4 ft., mkd. ¼ S17 BT.

A fir, 7" dia., bears S.22¾°W., 28.8 ft., mkd. ¼ S18 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description