

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Closing Cor. Sections 6 & 5 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Subdivisional Lines, T.32 S. R.5 W. As surveyed by Oscar F. Thiel, Deputy Surveyor, under contract No. 729. dated Dec. 24, 1900. (DCSO records Vol. 20 Page 8610-11)

I Set a Fir post, 3 ft. long, 4" square 24" in the ground, for closing cor. of secs. 5 and 6, marked CC T32S R5W on S. S5 on E. and S6 on W. faces, with 5 grooves on E., and 1 groove on W. faces; from which:

- A Fir, 30" dia. bears S.39°E., 33 lks. dist. mkd: T32S R5W S5 BT
- A Yew, 7" dia. bears S.63°W., 39 lks. dist. mkd: T32S R5W S6 BT

Douglas Co. Surveyors Office - George J. Wenderoth, Deputy Feb. 5, 1959 - C.S. File 49/92-4

Found - 30" Fir, S.39°E., 21.8 ft. Marks showing, Rescribe. 8" Yew, S.63°W., 25.7 ft. Down, Scribe Plain.
Set - 1" Iron Pipe.
New BT - 23" Cedar, N.8°53'W., 36.0 ft.

BLM Dependent Resurvey - J.S. Gawron & N.J. McDonald under Group #472, surveyed, June/July 1962 - (DCSO records Vol. 32 Page(s) 13246)

Found the closing cor. of Secs 5 and 6 as determined from original bearing trees:

- A Fir, 35" dia. bears S.39°E., 33 lks., with a healed blaze and CC S5 CSBT.
- A Yew, 9" dia. bears S.63°W., 39 lks. mkd. CC T32S R5W S6 BT.

At the corner point
Set an iron post, 30" long, 2½" dia. 26" in the ground, with brass cap mkd:

T 31 S
S 32

S 6 | S 5
CC
T32S R5W
1962

from which
A Fir, 6" dia. bears S.72°W., 58 lks., mkd: T32S R5W S6 CC BT.

(Cont. Next Page)

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Closing Cor. Secs 6 & 5 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady. May & June 1966 - C.S. File 54/25-27

Found - Iron Pipe & Brass Cap at Cor. (1962 Cadastral BC)

The Corner of Secs. 31|32 T31-5 bears West 114.7 ft.

30" D.Fir, now stump, S.39°E., 21.8 ft.

8" Yew, now stump, S.63°W., 25.7 ft.

23" Cedar, N.8°53'W., 36.0 ft. scribed "CC S6 CS BT"

7" Fir, S.70½°W., 38.5 ft. scribed "T31S R5W S6 H BT"

New BT -

12" Hemlock, S.78½°E., 27.5 ft. scribed "T32S R5W S5 CS BT"