

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8576)

Set Qr. sec. post, from which
A Laurel 10" dia., bears S.80°W., 32 lks.
A Laurel 4" dia., bears N.20°W., 41 lks.

W. F. Briggs, Co. Surveyor - For: H. Woodford and Ch. Aytch -July 1900 - Vol. 2 Page 97 and page 263

Set ¼ sec. cor., the original BT has been destroyed by fire. Mark new BT to wit:
Laurel 5" dia., bears S.20°W., 20 lks.
No other tree near.

George J. Wenderoth - 1952 - C.S. File 45/97

3/4" Pipe.
16" Madrona bears N.1°48'W., 46.5 ft.
13" Fir bears S.29°05'E., 12.4 ft.

BLM dependent resurvey by Joseph S. Gawron and Norman J. McDonald, under Group #472, surveyed June/July 1962 (DCSO records Vol. 32 Page(s) 13251-52)

Point for the ¼ sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 1/2 ins. dia., 26 ins. in the ground, with brass cap marked

T 32 S R 5 W

¼ $\frac{S\ 29}{S\ 32}$

1962

from which

A Fir 14" dia., bears N.57½°E., 26 lks. dist., mkd. ¼ S29 BT.

A Madrone 8" dia., bears S.4°E., 45 lks. dist., mkd. ¼ S32 BT.

From this point, an iron pipe 3/4" dia., firmly set, protruding 4" above ground, bears S.17½°W., 37 lks. dist. from which

A Fir 10" dia., bears S.32½°E., 19 lks. mkd. ¼ S CS BT.

A Madrone 18" dia., bears N.6 3/4°W., 70 lks. mkd. ¼ S CS BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas County Surveyors Office - Randall Smith; Stephen
Flause, crew - May 1, 1987 - C.S. File 62/45-24

Found - 1962 BLM 3/4" brass cap on a 2 1/2" O.D. iron pipe
protrudes 10" above ground.
A 3/4" I.D. iron pipe firmly set, protrudes 4" above
ground. (pipe was covered by duff)
14" now 18" dia., D.Fir with a fully healed single
blaze bears N.57 1/2°E., 17.2 ft. (agrees w/rec,
1964 BLM)
8" now 10" dia., Madrone with a fully healed single
blaze bears S.4°E., 29.7 ft. (agrees w/rec. 1964
BLM)
3/4" I.D. iron pipe set a 1/4 cor. per Wenderoth,
bears N.17 1/2°E., 24.0 ft. (Rec. S.17 1/2°W., 24.4 ft.
bearing apparently reversed in BLM records.
Dist. is a partial slope dist.)

Following bearing and distances taken to 3/4" iron pipe per
Wenderoth:

13" now 11" dia. D.Fir with a fully healed single
blaze bears S.29°E., 12.4 ft. (agrees w/Wenderoth
rec.)
18" still 18" dia. Madrone with a partially healed
double blaze with partial scribing and "BT"
visible, bears N.2°W., 46.5 ft. (agrees
w/Wenderoth rec.)
New BT - 18" dia. Madrone (Per Wenderoth) shows a double
blaze with partial scribing and "BT" in lower
blaze, bears N.4°E., 69.7 ft.
Corner lies on a southwesterly slope.
(Also see M 101-16 for Donald Bentz corner report)

Found OK by G. Nygren, Mar. 2001 - M136-79

Found OK by M. Hull, Feb. 2004 - M144-18
Fd. ok by K. DeGroot, 4/2007 - M152-74