

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8577)

-----  
Set Qr. sec. post, from which  
A Fir 10" dia., bears N.28°E., 14 lks.  
A Cedar 7" dia., bears S.8°W., 21 lks.

George J. Wenderoth - June 1952 - M 8-25

-----  
1/2" Iron pipe.  
12" Cedar bears N.65°E., 36.2 ft.  
12" Cedar bears S.47°05'E., 33.6 ft.

BLM Dependent resurvey by Arthur R. Rambo, & Francis Simon Cadastral Surveyors under Group No. 2143, surveyed May 2006/Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21688)

-----  
The ¼ sec. cor. of secs. 17 and 20, reestablished by proportionate measurement by Wenderoth, in 1952. There is no remaining evidence of the original cor., therefore this position is accepted as the cor.; monumented with an iron pipe, 3/4" dia., firmly set, projecting 8" above the ground, from which the remains of bearing trees mkd. by Wenderoth:

- A cedar, 22" dia., bears N.66¾°E., 36.2 ft., with a healed double blaze.
- A rotted, sawed cedar stump, size indeterminate, bears S.48¾°E., 33.4 ft., with a partially healed blaze, no marks visible.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over iron pipe, with brass cap mkd.

T 32 S R 5 W

¼  $\frac{S\ 17}{S\ 20}$

2006

from which a new bearing tree

A cedar, 11" dia., bears S.11°W., 20.5 ft., mkd. ¼ S20 BT. Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

Deposit a magnet in a white plastic case at the base of the stainless steel post.

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias	Description

BLM Dependent resurvey by Arthur R. Rambo, Cadastral Surveyor under Group No. 2179, surveyed July/Nov. 2007 - (DCSO records, Vol. 55 Page(s) 21688)

The 1/4 sec. cor. of secs. 17 and 20, reestablished by proportionate measurement by Wenderoth, in 1952. There is no remaining evidence of the original cor., therefore this position is accepted as the cor.; monumented with an iron pipe, 3/4" dia., firmly set, projecting 8" above the ground, from which the remains of bearing trees mkd. by Wenderoth:

A cedar, 22" dia., bears N.66 3/4°E., 36.2 ft., with a healed double blaze.

A rotted, sawed cedar stump, size indeterminate, bears S.48 3/4°E., 33.4 ft., with a partially healed blaze, no marks visible.

At the corner point

Set a stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, directly over iron pipe, with brass cap mkd.

T 32 S R 5 W

1/4 S 17  
S 20

2006

from which a new bearing tree

A cedar, 11" dia., bears S.11°W., 20.5 ft., mkd. 1/4 S20 BT. Each new bearing tree has a 2 1/2"x 1/4" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

Deposit a magnet in a white plastic case at the base of the stainless steel post.