

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original - W.H. Byars, under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 20 Page(s) 8589)

Set ¼ sec. post, from which
 A fir, 16" dia., bears N.10°W., 8 lks.
 A fir, 12" dia., bears S.25°E., 19 lks.

BLM Dependent resurvey by Arthur R. Rambo, & Francis Simon Cadastral Surveyors under Group No. 2143, surveyed May 2006/Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21691-2)

Point for the ¼ sec. cor. of secs. 8 and 17, at proportionate dist., there is no remaining evidence of the original cor. Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T32S R5W
 ¼ $\frac{S \ 8}{S \ 17}$
 2006

from which
 A fir, 18" dia., bears S.7°W., 25.3 ft., mkd. ¼ S17 BT.
 A fir, 14" dia., bears N. 78½° W., 34.6 ft., mkd. ¼ S8 BT.
 Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description
 Deposit a magnet in a white plastic case at the base of the stainless steel post.

Ron Quimby - Crew: N. Fromdahl, R Heichel & R Vincent - 5/2018 - C.S. File 65/101-34

Found - BLM brass cap (properly mkd)
 22" Fir S.7°W., 25.3 ft. good scar
 16" Fir N.78°W., 34.6 ft. good scar
 New BTs- 18" Fir N.51°E., 28.5 ft. scribed ¼ S8 BT
 12" Fir S.75°E., 6.3 ft. scribed ¼ S17 BT.
 Note - Compass decl. 15½°E.

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2925; Surveyed July/Oct. 2018 - (DCSO records Vol. 59 Page(s) 23756)

The ¼ sec. cor. of secs. 8 & 17, reported by Rambo and Simon in 2006-07, perpetuated by Quimby in 2018; monumented with a stainless steel post, 2½" dia., firmly set, projecting 4" above the ground, in a collar of stone, with brass cap (properly) mkd.
 from which bearing trees reported by Rambo and Simon
 Continued next page

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

A fir, 22" dia., bears S.7°W., 25.3 ft., with a healed blaze.

A fir, 16" dia., bears N.78½°W., 34.6 ft., with a healed blaze.

and bearing trees mkd. by Quimby

A fir, 17" dia., bears N.51¼°E., 28.3 ft., with scribe marks 1/4 S8 BT visible on open blaze.

A fir, 11" dia., bears S.77¼°E., 6.5 ft., with scribe marks 1/4 S17 BT visible on open blaze.

The geographic position in NAD 1983 (2011)
Latitude: 42°47'51.04" N. Longitude: 123°19'02.45" W.

2