

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 20 Page(s) 8608)

Set a granite stone 14x10x8 ins., 10" in the ground, for ¼ sec. cor., marked ¼ on N. side, from which
A Fir 5" dia., bears N.17°W., 27 lks. mkd. ¼ S5 BT.
A Fir 12" dia., bears S.49°W., 19 lks. mkd. ¼ S8 BT.
This corner stands near a bottom of ravine.

BLM dependent resurvey by Joseph S. Gawron and Norman J. McDonald, under Group #472, surveyed June/July 1962 (DCSO records Vol. 32 Page(s) 13257)

The ¼ sec. cor., determined from the original bearing trees:
A Fir 8" dia., bears N.17°W., 27 lks. dist., mkd. BT.
A Fir 13" di., bears S.49°W., 19 lks. dist. mkd. ¼ S8 BT
At the corner point
Set an iron post, 30 ins. long, 2 1/2 ins. dia., 10 ins. in the ground, to solid rock, and in a mound of stone, 5 ft. base to top, with brass cap marked
T 32 S R 5 W
¼ $\frac{S}{S}$ $\frac{5}{8}$
1962
from which
A Fir 10" dia., bears N.1½°W., 67 lks., mkd. ¼ S5 BT.
A Fir 20" dia., bears S.37½°W., 63½ lks., mkd. ¼ S8 BT.

James McIntosh, Oregon Dept. of Forestry - 3/2006 - M150-23

Found - BLM P/C IN MS, 1962 (in place)
12" fir (1901) S.49°W., 19 lks (now roothole in place, partial scribes visible on rotted stub lying down hill)
10" fir N.1½°W., 67 lks (now 12" in place, face closed, BLM BTT)
20" fir S.37½°W., 63½ lks (now 27" in place, face closed, BLM BTT)
New - WP N.47°E., 3.95' to base.
WP S.32°E., 2.90' to base

Fd. OK 5/2018 by R. Quimby C.S. File 65/101-11

continued next page

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2925; Surveyed July/Oct. 2018 - (DCSO records Vol. 59 Page(s) 23757)

The ¼ sec. cor. of secs. 5 and 8, reported by Gawron and McDonald in 1962, monumented with an iron post, 2 1/2" dia., firmly set, projecting 10" above the ground, in a collar of stone, with brass cap (properly) mkd.

from which bearing trees reported by Gawron and McDonald

A fir, 31" dia., bears S.38¼°W., 41.9 ft., with a healed blaze. (Record, S.37½°W.)

A fir, 12" dia., bears N.1½°W., 44.2 ft., with a healed blaze.