

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 5 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM survey by Joseph Gawron and Norman McDonald, under Group #472 - Surveyed, June/July 1962 (DCSO records Vol. 32 Page(s) 13259-60)

Point for the S. $\frac{1}{4}$ sec. cor. of sec. 5 only, at mid-point, longitudinally, on the N. bdy. of sec. 5.
Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. dia., 24 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd:

$\frac{1}{4}$ S 5
T 32 S R 5 W
1962

from which

A Cedar 12" dia., bears S.15 $\frac{1}{2}$ °E., 35 lks. dist., mkd. $\frac{1}{4}$ S5 BT.

A Fir 10" dia., bears S.88°W., 23 lks. dist., mkd. $\frac{1}{4}$ S5 BT.

Survey by T.H. Mehl, III - For: Robert Dollar Co. - June 16, 1967 - C.S. File 55/15-4

Found - No trace of 1962 Cadastral brass cap.
10" D.Fir S.83°W. 23 lks. knocked over by logging.
12" I.Cedar S.15 $\frac{1}{2}$ °E., 35 lks. scribing buried under logs.

Set 1 $\frac{1}{2}$ x 40" Iron Pipe, 32" into the ground, from which:
Rescribed the 12" I.Cedar " $\frac{1}{4}$ S RS 749 BT", four feet above ground.