

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 274100

PRIMARY CORNER DESCRIPTION C C for Secs. 4 and 5 only, T33-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (Cor. set June 21, 1894) (DCSO records Vol. 21 Page(s) 8988)

Set a basaltic stone 12 x 10 x 6 ins., 8" in the ground for closing cor. to secs. 4 and 5 marked C C with 2 notches on W. and 4 notches on E. edges, from which
A Fir 48" dia., bears S.34°30'E., 132 lks. dist., marked T33S R5W S4 BT.
A W.Fir 30" dia., bears S.51°W., 169 lks. marked T33S R5W S5 BT.
A Fir 6 ft. dia., bears N.44°45'E., 61 lks. dist., marked T33S R5W C C S4 and 5 BT.

George J. Wenderoth - For: Ge. Newman - 1953 - C.S. File 49/112

Closing cor. to secs. 4 and 5. Find:
60" Fir S.34°30'E., 87.1 ft., stump scribed.
80" Fir S.51°W., 41.9 ft.
Drive bed rail for corner.

Survey by Norman D. Price For: Dollar and Patterson Lumber Co. July 1953 - C.S. File 41/184

The closing cor. of secs. 4 and 5, T33S R5W, monumented with a 2" angle iron from a bed rail, 20" above ground, firmly set, from which
A sawed Fir stump 55" dia., bears S.31°E., 129 lks. dist., with old blaze healed.
A D.Fir 60" dia., bears S.52½°W., 62 lks. dist., with partial scribe marks visible on old blaze.
A W.Fir 18" dia., bears S.32°W., 17 lks. dist., mkd. CC 4 & 5 CS BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - July 1967 - C.S. File 53/52-56

Found - Bedrail at the approx. corner, N.54°E., 6.4 ft. from corner.
48" now 56" D.Fir stump S.34½°E., 87.1 ft., shows scribing "T".
No trace of other BTs.
Set Brass cap at C.C. mkd:
(Cont. Next Page)

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 274100

PRIMARY CORNER DESCRIPTION CC for Secs. 4 & 5 only, T33-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

County Surveyors Office
T 32 S

S 5 | S 4 R5W
T 33 S
1967

New BTs -8" Hemlock S.78°W., 28.5 ft. mkd. T33S R5W CS BT.
10" Hemlock S.21°E., 35.0 ft. mkd. T33S R5W S4 CSBT
This corner lies in middle of old cat road and 40 ft. west of
small creek.
(Believe bed rail was moved from position used by Price. See
C.S. File 41/184 and C.S. 53/52)

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 7/6/2000 - C.S. File 66/16-17

Found - 1967 DCS0 BC/IP, properly marked, protrudes 6" above
ground.
1953 Bed rail protrudes 12" above ground bears
N.54°E., 6.4 ft. from BC/IP.
48" now 54" dia., 3 ft. high D.Fir stump previously
opened scribing visible "4" bears S.34½°E., 87.1
ft. OBT
8" now 15" dia., Hemlock with a partially healed
double blaze. Illegible scribing visible bears
S.78°W., 28.5 ft. 1967
10" now 15" Hemlock with healed double blaze, bears
S.21°E., 35.0 ft. 1967

New - 20" dia., Hemlock double blazed & scribed "T33S R5W
S4 CS BT" bears East, 11.4 ft.

Note - Possible orig. note error fd. large D.Fir stump
tipped out of ground, root hole bears approx.
S.51°W., 40.3 ft. Possible OBT would of fallen on
blaze.
Orig. BT Record:
30" W.Fir S.51°W., 111.5 ft.
6 ft. Fir N.44 3/4°E., 40.3 ft.
(Bearings possibly switched?)
No evidence of 30" W.Fir fd.
A check of the micro fiche showing 1894 hand written
notes does not reveal an error.

Found OK by M. Hull, Feb. 2004 - M144-18

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor,
under Group No. 3006; Surveyed April 2021/Nov. 2022 - (DCS0
records Vol. 59 Page(s) 24141-2)

continued next page

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 274100

PRIMARY CORNER DESCRIPTION C C for Secs. 4 and 5 only, T33-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The original closing cor. of secs. 4 and 5, at intersection with the N. bdy. of the Tp. (Seventh Standard Parallel South), perpetuated by Wenderoth, in 1953; subsequently perpetuated by the Douglas County Surveyor's Office in 1967; and again in 2000; monumented with an iron post, 1½" dia., firmly set, projecting 6" above the ground, with brass cap (properly) mkd.

from which the remains of an original bearing tree

A rotted fir stump, size indeterminate, bears S.34½°E., 87.1 ft., with illegible scribe marks visible on open blaze.

and a BT mkd. by the Douglas County Surveyor's Office in 1967

A hemlock, 17" dia., bears S.21¾°E., 34.8 ft., with a healed double blaze.

and a BT mkd. by the Douglas County Surveyor's Office in 2000

A hemlock, 25" dia., bears N.88½°E., 12.2 ft., with illegible scribe marks visible on partially healed double blaze.

and a new bearing tree

A hemlock, 10" dia., bears S.46°W., 7.5 ft., mkd. T33S R5W S5 CC BT.

Note - Each new BT has a 2½"x¼" magnetic nail (Mag Nail) driven at the base on right side center and each monument established or reestablished has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description.

From this cor., a point established by Wenderoth, bears N.52°18'55"E., 6.43 ft., monumented with a welded angle iron, firmly set, projecting 10" above the ground, and was not utilized for control in the course of this survey. It appears that the welded angle iron was moved from the position that it was originally established.