

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 32 and 33 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 20 Page(s) 8599)

-----  
At point of intersection, set a dogwood post, 3 ft. long, 4" sq., 24" in the ground for closing corner of secs. 32 and 33, marked C C T32S R5W on N.; S33 on E.; and S32 on W. faces; with 4 grooves on E., and 2 grooves on W. faces, from which  
A Fir 72" dia., bears N.61°E., 33 lks. marked T32S R5W S33 BT.  
A Maple 10" dia., bears N.9°W., 16 lks. marked T32S R5W S32 BT.

George J. Wenderoth - For: Geo. Newman - 1953 - C.S. File 49/112

-----  
Find corner to secs. 32 and 33, T32S R5W. Find:  
84" Fir N.61°E., 21.7 ft. No scribe shows.  
Old stake marked C.C. 32 & 33.  
Drive 3/4" iron rod for corner. Mark  
7" Maple N.24°15'W., 42.0 ft.

Survey by Norman Price - For: Dollar and Patterson Lumber Co. July 1953 - C.S. File 41/184

-----  
The closing cor. of secs. 32 and 33, T32S R5W, monumented with an iron bolt, 1" dia., 6" above ground, firmly set, from which  
A D.Fir 60" dia., bears N.60°E., 35 lks. dist., mkd. CC 33 CS BT.  
A Maple 8" dia., bears N.26°W., 63 lks. dist., mkd. CC 32 CS BT.  
Find no evidence of the Ives and Hyde cor. of secs. 4, 5, 32 and 33.

Douglas Co. Surveyors Office - John M. Powell, Joe Brady, crew - August 1967 - C.S. File 53/52-49

-----  
Found - 60" Fir stump N.59°E., 22.1 ft. mkd. CC T32S R5W S33 CS BT.  
1" Axle at corner set by Norman Price, 1953 (C.S. File 41/184)  
New BTs -10" D.Fir N.24°E., 20.6 ft. mkd. CC T32S R5W S33 CS BT.  
12" D.Fir N.1°W., 17.2 ft. mkd. CC T32S R5W S32 CS BT.

continued next page

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 32 and 33 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 7/6/2000 - C.S. File 66/16-18  
-----

CONDITION REPORT

Found - 3/4" axle protruding 4" above ground. 1953  
72" now 48" dia., rotted 3 ft. high D.Fir stump no  
scribing or blazes remaining, bears N.61°E., 24.8  
ft. (Orig. rec. N.61°E., 21.8 ft. probable face  
measurement) OBT  
7" now 16" dia., Maple with a fully healed single  
blaze bears N.26°W., 42.0 ft. 1953  
10" now 22" dia., D.Fir with a fully healed single  
blaze, bears N.24°E., 20.6 ft. 1967  
12" now 26" dia., D.Fir with a fully healed single  
blaze bears N.1°W., 17.2 ft. 1967

Found OK by M. Hull, Feb. 2004 - M144-18  
Fd. OK by D. Edwards, 7/2010 - C.S. File 65/69-34

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor,  
under Group No. 3006; Surveyed April 2021/Nov. 2022 - (DCS0  
records Vol. 59 Page(s) 24114-5)  
-----

The closing cor. of secs. 32 and 33, T32S R5W perpetuated by  
Wenderoth, in 1953; subsequently perpetuated by the Douglas  
County Surveyor's Office in 1967, bears North, 4.43 ft.;  
monumented with an axle, 1" dia., firmly set, projecting 5"  
above the ground, from which the remains of an original BT

A rotted fir stump, size indeterminate, bears N.61°E.,  
21.8 ft., no marks visible.

and a bearing tree mkd. by Wenderoth

A maple, 18" dia., bears N.26¼°W., 42.3 ft., with a healed  
blaze.

and BTs mkd. by the Douglas County Surveyor's Office

A fir, 30" dia., bears N.23½°E., 20.8 ft., with a healed  
blaze.

A fir, 32" dia., bears N.0¾°W., 17.2 ft., with a healed  
blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the  
ground, directly over the axle, with brass cap mkd.

CC  
T 32 S R 5 W  
S 32 | S 33  
S 4  
T 33 S R 5 W  
2021