

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8572)

-----  
Set post cor. to secs. 28, 29, 32 and 33 on NE. descent, from which

- A Laurel 12" dia., bears S.20°W., 34 lks.
- A Laurel 5" dia., bears N.62°W., 21 lks.
- A Laurel 6" dia., bears N.23°E., 20 lks.
- A Laurel 4" dia., bears S.63°E., 19 lks.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 20 Page(s) 8596)

-----  
The old cor. has disappeared and I reestablish the same by setting a Fir post, 3 ft. long, 3" sq., 24" in the ground, in mound of stone, marked T32S S28 on NE.; R5W S33 on SE.; S32 on SW.; and S29 on NW. faces; with 1 notch on S. and 4 notches on E. edges, from which

- A Fir 24" dia., bears N.53°E., 27 lks. mkd. T32S R5W S28 BT. New BT.
- A Fir 30" dia., bears S.38°E., 19 lks. mkd. T32S R5W S33 BT. New BT.
- A Laurel 12" dia., bears S.20°W., 34 lks. mkd. T32S R5W S32 BT. Old BT.
- A Fir 30" dia., bears N.28°W., 38 lks. mkd. T32S R5W S29 BT. New BT.

BLM dependent resurvey by Joseph S. Gawron and Norman J. McDonald, under Group #472, surveyed June 1962 (DCSO records Vol. 32 Page(s) 13247)

-----  
The Sec. cor., determined at record bearing and distance from the original bearing trees:

- A Fir 28" dia., bears N.53°E., 27 lks. dist., with a healed blaze. (mkd. by Thiel in 1901)
- A Fir snag 36" dia., bears S.38°E., 19 lks. dist., mkd. T R on face of partially opened blaze. (mkd. by Thiel in 1901)
- A down and rotted Madrone bears S.20°W., 34 lks. dist., (mkd. by Lake and Hyde in 1855)
- A Fir 36" dia., bears N.28°W., 38 lks. dist., mkd. T (mkd. by Thiel in 1901)

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. dia., 26 ins. in the ground, with brass cap marked

(Cont. Next Page)

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T 32 S R 5 W  
S 29 | S 28  
S 32 | S 33  
1962

from which

- A Fir 15" dia., bears S.49½°E., 118 lks. dist., mkd. T32S R5W S33 BT.
- A Madrone 12" dia., bears S.13°W., 73 lks. dist., mkd. T32S R5W S32 BT.
- A Fir 36" dia., bears N.85°W., 69 lks. dist., mkd. T32S R5W S29 BT.

Found OK by G. Nygren, Mar. 2001 - M136-79