

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8572)

Set Qr. sec. post, from which
A Laurel 6" dia., bears N.51°E., 59 lks.
A Laurel 7" dia., bears N.74°W., 50 lks.

W.F. Briggs, May 22, 1888 - F.B. 99 Pg. 50

One old BT gone.
Laurel 12" S.15°W., 30 lks.
Fir 5" North, 8 lks.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 20 Page(s) 8619)

Set temp. ¼ sec. cor. on E. side of mountain; All traces of bearing trees have disappeared.

George J. Wenderoth - Nov. 1, 1959 - C.S. File 49/188

¼ cor. as found.
1¼" iron pipe.
12" Fir S.86°15'W., 21.0 ft.
12" Fir N.70°36'E., 39.4 ft.

BLM dependent resurvey by Joseph S. Gawron and Norman J. McDonald, under Group #472, surveyed June 1962 (DCSO records Vol. 32 Page(s) 13248)

Point for the ¼ sec. cor. of sec. 29 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 1/2 ins. dia., 26 ins. in the ground, with brass cap marked

T 32 S R 5 W
¼ |
S 29 |
1962

from which
A Fir 12" dia., bears S.71°W., 62 lks. dist., mkd. ¼ S29 BT.
No other suitable tree available.

From this point, an iron pipe, 1" dia., firmly set, protruding 10" above ground, bears S.17¼°W., 0.04 chs. dist., (Cont. Next Page)

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 29

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

from which locally established bearing trees
A Fir 12" dia., bears N.70°E., 60½ lks. dist. mkd. ¼ S28
RS 33 BT.
A Fir 12" dia., bears S.86°W., 32 lks. dist., mkd. ¼ S29
RS 33 BT.

Fd. brass cap & BTs by M. Hull 9/1975 M58-30
Fd. brass cap, July 1990, M 110-66

Gregg Neitsch - For: Siskiyou Timberlands LLC - 3/2021 -
M179-30

Found - Standard BLM monument stamped "T32S R5W ¼ S29 1962"
from which bears:
DF stump, rotted, S.78°W., 20.0' (S.86°W., 21.1'
from iron pipe)
18" DF stump, S.70°W., 39.9' (S.71°W., 40.9').
1" I.D. iron pipe S.21°33'W., 2.34' (S.17¼°W. 2 64')
6" diam. wood fence post, N.36¼°W., 2.0'.

Note - This monument was set as the ¼ corner to section 29
only however, it has since been accepted as the
corner to section 28 also (see R1 - M58-30).