

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8571)

Set post cor. to secs. 20, 21, 28 and 29, from which
A Fir 8" dia., bears S.8°E., 18 lks.
A Fir 8" dia., bears S.37°W., 40 lks.
A Fir 3" dia., bears N.45°W., 26 lks.
A Maple 3" dia., bears N.62°E., 26 lks.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 20 Page(s) 8627) (and page 8619)

At the sec. cor., the post being gone, I reestablished the same by setting a granite stone 14x10x10 ins., 10" in the ground for the sec. cor., marked with 2 notches on S. and 4 notches on E. edges, witnessed as described by the surveyor general.

George J. Wenderoth - July 1956 - C.S. File 47/94

Found angle iron at corner point.
Marked two trees:
10" Fir N.74°45'W., 45.3 ft.
34" Pine S.55°30'E., 72.1 ft.

BLM dependent resurvey by Joseph S. Gawron and Norman J. McDonald, under Group #472, surveyed June 1962 (DCSO records Vol. 32 Page(s) 13248-49)

The Sec. cor., which is monumented with a "T" iron, 2 x 2 ins., firmly set, protruding 4" above ground. This position is harmoniously related to existing original corners, has long been recognized as the cor. by adjacent land owners, and is accepted as the best existing evidence of the position of the original corner, from which trees recorded by the Douglas Co. Surveyors Office:

A Y.Pine 34" dia., bears S.55½°E., 109 lks. dist., mkd.
T32S R5W S28 CS BT.
A Fir 10" dia., bears N.75 3/4°W., 69 lks. dist., mkd.
T32S R5W S20 CS BT.

At the corner point
Set an iron post, 30" long, 2½" dia., 26" in the ground, with brass cap mkd.

(Cont. Next Page)

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

T 32 S R 5 W
S 20 | S 21
S 29 | S 28
1962

from which

A Live Oak 6" dia., bears N.82°E., 110 lks. dist., mkd. T32S R5W S21 BT.

An Ash 8" dia., bears S.45°E., 143 lks. dist., mkd. T32S R5W S28 BT.

An iron pipe 1½" dia., 48" long, set 36" in the ground, bears N.19°W., 46 lks. dist.

Reset the "T" iron alongside the iron post.

BLM resurvey by Virgil L. Stanger, Cadastral Surveyor, under Group #1145, surveyed May/Aug. 1983 - (DCSO records Vol. 47 Page(s) 17883-84)

The Sec. cor., monumented with an iron post, 2½" dia., firmly set, protruding 4" above ground, with 1962 brass cap, from which bearing trees mkd. by the Co. Surveyors Office

A Ponderosa Pine 45" dia., bears S.58°E., 111 lks. dist., with healed blaze. (Rec. S.55½°E., 109 lks.)

A Fir 18" dia., bears N.78°W., 69 lks. dist., with healed blaze. (Rec. N.75 3/4°W.)

and bearing tree and object mkd. by Gawron an McDonald:

An Ash, 8" dia., bears S.49½°E., 143 lks. dist., with healed blaze. (Rec. S.45°E.)

An iron pipe 1½" dia., firmly set, projecting 12" above ground, bears N.21 3/4°W., 46 lks. dist. (Rec. N.19°W.) and a new bearing tree:

A Cedar 6" dia., bears N.62½°E., 115 lks. dist., mkd. T32S R5W S21 BT.

No other suitable trees available within limits. Corner is located in a fence, extends N. and S.

From this point, United States Coast and Geodetic Survey triangulation station "GOAT" bears N.29°30'E., 254.89 chs. monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap mkd. GOAT USC&GS 1963.

Douglas Co. Surveyors Office - Randall Smith, Party Chief, Stephen Flause, notekeeper - Sept. 17, 1985 - C.S. File 62/29-20

Found - 1962 BLM brass cap, properly mkd., on a 2½" dia. I.P. firmly set and protruding 5" above ground.

(Cont. Next Page)

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A 3¼" x 2½" "T" iron of unknown origin, first recorded by Wenderoth, is firmly set at southeast edge of cap and protrudes 5" above ground.
10" Fir now a double trunked 18" and 35" DBH D.Fir with a fully healed blaze on the smaller trunk bears N.78°W., 47.7 ft. to root crown (Rec. N.74°45'W., 45.3 ft. is to center of scribed trunk)
34" Pine now a 46" DBH Pine with a fully healed single blaze bears S.58°E., 72.8 ft. (Rec. S.55°30'E., 72.1 ft. dist. is good to face of blaze.)
An Ash, now a 16" DBH Ash, having a partially healed blaze with illegible scribing visible bears S.49½°E., 94.8 ft. (Rec. S.45°E., 94.4 ft. dist. good to face of blaze.) (BLM)
An iron pipe 1½" dia., now a 1¼" O.D. iron pipe protruding 12" from ground, bears N.21°W., 30.4 ft. (Rec. N.19°W., 30.4 ft.) (BLM)
An unrecorded new bearing tree, an 8" DBH Incense Cedar with a single partially healed blaze, scribed "T32S R5W S21 BT" bears N.62°E., 76.0 ft.
Monument position accepted as found.
New Accessories:
 Bearing tree tags marked to indicate changes noted in accessories found.
Monument lies 350 ft. ± South from County Rd. #303 in a North-South fence line and at the East edge of an open field.

Fd. OK, Max Hull, Sept. 1985, M 99-33 and C.S. File 63/24
FD. OK by R.Dolan, April 1995, M 119-55
FD. OK by R. Wytcherley - Jan. 25, 1997 - M 126-47
Fd. OK by R. Wytcherley - May 5, 2001 - M138-11
Fd. Ok by Ray Wytcherley, July 2005 - M146-24
Fd. Ok by Ray Wytcherley, July 2013 - M165-57