

PRIMARY CORNER DESCRIPTION Sec Cor for 16, 17, 20 and 21

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO recs Vol 20 Pg 8570)

- 
- Set post cor. to secs. 16, 17, 20 and 21, from which
- A Laurel 7" dia., bears N.68°W., 26 lks.
  - A Laurel 10" dia., bears S.25°W., 41 lks.
  - A B.Oak 7" dia., bears S.73°E., 34 lks.
  - A Laurel 3" dia., bears N.25°E., 46 lks.

W. F. Briggs, Co. Surveyor - For: H.L. Wilson (Levens Estate) July 1900 - Vol. 2 Page 96

-----

Set post as per original BT.

George J. Wenderoth - 1952 - M 7-53 and M 8-25

- 
- 1" I.Pipe
- 12" Maple bears S.25°33'E., 101.5 ft.
  - 14" Maple bears S.77°30'W., 86.8 ft.
  - 16" Maple bears N.52°W., 22.3 ft.
  - 14" Madrone bears N.18°30'E., 88.6 ft.

BLM Dependent resurvey by Arthur R. Rambo, & Francis Simon Cadastral Surveyors under Group No. 2143, surveyed May 2006/Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21676)

-----

The cor. of secs. 16, 17, 20, and 21, restored by Wenderoth, in 1952. There is no remaining evidence of the original cor., therefore this position is accepted as the cor.; monumented with an iron T post, 5 ft. long, projecting 4 ft. above the ground, from which bearing trees mkd. by Wenderoth:

- A madrone, 27" dia., bears N.17¾°E., 87.7 ft., with a healed blaze.
- A maple, 17" dia., bears S.26¾°E., 99.1 ft., with a healed blaze.
- A maple, 16" dia., bears S.77°W., 85.2 ft., with a healed blaze.
- A maple, 18" dia., bears N.51½°W., 21.7 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd. T 32 S R 5 W

S 17 | S 16  
S 20 | S 21  
2006

Deposit a magnet in a white plastic case at the base of the stainless steel post, and set T post alongside.