

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8578)

-----  
Set Qr. sec. post on W. slope, from which  
A Laurel 7" dia., bears N.73°E., 33 lks.  
A Fir 24" dia., bears S.30°W., 73 lks.

George J. Wenderoth - July 1952 - M 7-53

-----  
1" Iron pipe.  
11" Madrona S.51°25'E., 17.6 ft.  
8" Madrona N.38°30'W., 11.0 ft.

Fd. OK, A. Rambo, March 1992, M 114-78

BLM Dependent resurvey by Arthur R. Rambo, & Francis Simon Cadastral Surveyors under Group No. 2143, surveyed May 2006/Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21678)

-----  
The ¼ sec. cor. of secs. 16 and 17, reestablished by proportionate measurement by Wenderoth, in 1952, and utilized by Rambo, in 1992. There is no remaining evidence of the orig cor., therefore this position is accepted as the cor.; monumented with an iron pipe, 1" dia., firmly set, projecting 3" above the ground, from which BTs mkd. by Wenderoth:

A madrone, 23" dia., bears S.50¼°E., 17.7 ft., with a healed blaze.

A madrone, 19" dia., bears N.40°W., 11.3 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over iron pipe, with brass cap mkd.

T 32 S R 5 W  
¼  
S 17 | S 16  
2006

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner falls on W. edge of N. and S. dirt road.

Kris DeGroot - March 2008 - C.S. File 65/63-13

-----  
Condition report  
Reported finding a 2006 BLM brass cap, no new trees.