

PRIMARY CORNER DESCRIPTION Sec Cor for 8, 9, 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO recs Vol 20 Pg 8578)

Set post cor. to secs. 8, 9, 16 and 17, from which
A Fir 5" dia., bears N.57°E., 29 lks.
A Fir 7" dia., bears N.38°W., 42 lks.
A Fir 6" dia., bears S.44°W., 29 lks.
A Maple 6" dia., bears S.12°E., 33 lks.

George J. Wenderoth - June 1952 - M 8-25 and M 7-53

Car Axle
18" Alder bears S.40°30'W., 65.5 ft.
10" Yew bears S.32°30'E., 32.6 ft.
14" Fir bears N.43°06'E., 84.8 ft.
6" Fir bears N.15°24'W., 33.7 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - July 1967 - C.S. File 53/52-39

Found - Axle at section corner.
18" Alder now stob, S.40½°W., 65.5 ft, scribe visible "T"
10" Yew now down, S.32½°E., 32.6 ft., scribe visible.
14" Fir now down, N.43°E., 84.8 ft., shows scar.
6" now 9" Fir N.15½°W., 33.7 ft., shows good scar.
New BTs -10" D.Fir N.9°E., 36.2 ft. mkd. T32S R5W S9 CS BT.
10" Hemlock S.85°W., 30.1 ft. mkd. T32S R5W S17 CS BT.
24" Maple, South, 41.0 ft. mkd. T32S R5W S16 CS BT.
This corner lies approx. 65.0 ft. N. of creek and 140.0 ft. S. of logging road.

Fd. OK, by A. Rambo, March 1992, M 114-78
Fd. car axle, 4 BTs & unrecorded alum. post by James McIntosh 5/2006 - M150-56

BLM Dependent resurvey by Arthur R. Rambo, & Francis Simon Cadastral Surveyors under Group No. 2143, surveyed May 2006/Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21679-80)

The cor. of secs. 8, 9, 16, and 17, restored by person(s) unknown, perpetuated by Wenderoth, in 1952, and perpetuated by the Douglas County Surveyor's Office, in 1967, and utilized by Rambo, in 1992. There is no remaining evidence of the original cor., therefore this position is accepted as the cor.; monumented with an axle, 1" dia. firmly set, cont.

PRIMARY CORNER DESCRIPTION Sec Cor for 8, 9, 16 and 17

Alias	Description
Alias	Description
Alias	Description
Alias	Description

projecting 10" above the ground, from which a bearing tree mkd. by Wenderoth:

A fir, 23" dia., bears N.16½°W., 33.7 ft., with a healed blaze.

and remains of bearing trees mkd. by the Douglas County Surveyor's Office

A fir, 25" dia., bears N.7¾°E., 36.6 ft., with a healed blaze.

A maple, 30" dia., bears S.1/2°E., 40.8 ft., with a healed blaze.

A hemlock snag, 25" dia., bears S.84½°W., 30.1 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, directly over axle, with brass cap mkd.

T 32 S R 5 W
S 8 | S 9
S 17 | S 16
2006

from which a new bearing tree

A fir, 17" dia., bears S.55½°W., 44.0 ft., mkd. T32S R5W S17 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

Deposit a magnet in a white plastic case at the base of the stainless steel post.