

PRIMARY CORNER DESCRIPTION Sec Cor for 4, 5, 8 and 9

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Original - W.H. Byars, under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 20 Page(s) 8587)

 Set post cor. to secs. 4, 5, 8 and 9, from which
 A Fir 36" dia., bears N.52°E., 106 lks.
 A Cedar 6" dia., bears S.70°E., 50 lks.
 A Fir 36" dia., bears S.65°W., 33 lks.
 A Laurel 8" dia., bears N.45°W., 85 lks.

GL0 survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 20 Page(s) 8603-04)

 The cor. of secs. 4, 5, 8 and 9, which is an old post, badly decayed; I replace the cor. by setting a granite stone 14x12x7 ins., 10" in the ground, marked with 5 notches on S. and 4 notches on E. edges, from which
 A Laurel 10" dia., bears N.11°E., 22 lks. mkd. T32S R5W S4 BT.
 A Fir 7" dia., bears S.21°E., 142 lks. mkd. T32S R5W S9 BT
 A Laurel 12" dia., bears S.55°W., 75 lks. mkd. T32S R5W S8 BT.
 A Fir 18" dia., bears N.9°W., 40 lks. mkd. T32S R5W S5 BT.
 The old bearing trees are burnt down, but their stumps still remaining.

BLM dependent resurvey by Joseph S. Gawron and Norman J. McDonald, under Group #472, surveyed June/July 1962 (DCSO records Vol. 32 Page(s) 13249-50)

 The Sec. cor., determined from bearing trees mkd. by Thiel in 1901:
 A Fir 23" dia., bears S.19°E., 142 lks. dist., with a healed blaze. (Rec. bearing S.21°E.)
 A Madrone 25" dia., bears S.57°W., 75 lks. dist., mkd. T32S R5W S8 BT. (Rec. bearing S.55°W)
 A Fir 35" dia., bears S.11°W., 40 lks. dist., with chopped and rotted face. (Rec. bearing N.9°W.)

At the corner point
 Set an iron post, 30" long, 2½" dia., 8" in the ground, to solid rock, supported in a mound of stone, 5 ft. base to top, with brass cap mkd.

T	32	S	R	5	W
	S	5	S	4	
	S	8	S	9	
					1962

from which
 (Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 4, 5, 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 10" dia., bears N.66°E., 18 lks. mkd. T32S R5W S4 BT
A Fir 10" dia., bears S.12°E., 47 lks. mkd. T32S R5W S9 BT
A Fir 6" dia., bears S.43°W., 36 lks. mkd. T32S R5W S8 BT
A Fir 14" dia., bears N.13½°W., 107 lks mkd T32S R5W S5 BT

Bruce R. Rogers, Deputy - Wit: M. Stone and Wm. Stoffel -
June 25, 1965 - C.S. File 53/52-59

Found - Orig. Madrone now 25", S.57°W., 75 lks., shows face.
Orig. Fir now 35", N.11°W., 40 lks., shows rotted
face.
10" Fir N.66°E., 11.9 ft., full scribing visible.
10" Fir S.12°E., 31.0 ft., full scribing visible.
(has been cut)
14" Fir N.13½°W., 70.3 ft., full scribing visible.
No trace of 1962 SW tree.
Brass cap lost in logging.

Set Brass cap at cor. mkd: County Surveyors Office
T 32 S R 5 W
S 5 | S 4
S 8 | S 9
1965

FD. BC & 5 BTs by James McIntosh, May 2006 - M150-56

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor,
under Group No. 2925; Surveyed July/Oct. 2018 - (DCSO records
Vol. 59 Page(s) 23755-6)

The cor. of secs. 4, 5, 8, & 9, reported by Gawron and
McDonald in 1962, perpetuated by the Douglas Co Surveyor's
Office in 1965 monumented with an iron post, 1" dia., firmly
set, projecting 10" above the ground, with brass cap
(properly) mkd.

from which bearing trees reported by Gawron and McDonald
A fir, 22" dia., bears N.66°E., 11.9 ft., with a healed
blaze.
A fir, 44" dia., bears S.12°E., 31.0 ft., with a healed
blaze.
A madrone, 32" dia., bears S.55¾°W., 47.9 ft., with scribe
marks BT visible on partially healed blaze. (Original)
(Record, S.57°W., 49.5 ft.)
A fir, 24" dia., bears N.14½°W., 70.6 ft., with a healed
blaze. (Record, N.13½°W.)
A fir, 49" dia., bears N.12½°W., 27.4 ft., with a healed
blaze. (Original) (Record, N.11°W., 26.4 ft.)

