

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 336100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 4 only, T33-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Norman D. Price - For: Dollar and Patterson Lumber Co. - July 27-28, 1953 - C.S. File 41/184

This corner lies mid-point between the two North closing corners of Sec. 4 and 46.22 chains from each one.

Set an iron pipe 3 ft. long, 1½" dia., 28" in the ground, mkd. RS33, from which

A D.Fir 14" dia., bears S.53½°E., 56 lks. mkd. ¼ S4 RS33 BT.

A D.Fir 24" dia., bears S.21°W., 43 lks. mkd. ¼ S4 RS33 BT

Corner OK, DCS0, J. Powell, Sept. 16, 1967 C.S. File 53/52-42

Gregg Neitsch - For: John Hancock Life Insurance Co - 12/2022 - M181-58

Set - 5/8"x30" rebar (24" in the ground) with 2½" dia. alum. cap stamped "PLS 77662" by intersection, from which:

1½" dia. galvanized iron pipe, tagged "RS 33", N.0°47'08"W., 6.30' (C.S. File 41/184)

24" dia., D.Fir, rotted stump, S.26°19'W., 22.9'

28" dia., D.Fir, with healed blaze, S.63°44'E., 32.9'

New - 11" dia., D.Fir, S.54°35'W., 42.1'

10" dia., D.Fir, S.7°36'W., 21.8'

10" dia., Madrone, N.55°19'W., 33.0'