

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 20 Page(s) 8596)

Set a granite stone 18x12x6 ins., 12" in the ground for ¼ sec. cor. marked ¼ on N. face, from which
A Y.Pine 40" dia., bears N.68¼°E., 113 lks. mkd. ¼ S28 BT
A B.Oak 28" dia., bears S.72°E., 80 lks. mkd. ¼ S33 BT.
This cor. stands 250 ft. above stream.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - July 1967 - C.S. File 53/52-53

Found - Orig. 40" now 48" Pine, N.68¼°E., 68.0 ft., shows scar. Tree burnt out.
Orig. 28" B.Oak now dead, S.72°E., 52.8 ft. scribe visible "B"
No trace of stone at ¼ corner.

Set Brass cap at cor. mkd: County Surveyors Office
T 32 S R 5 W
S 28
S 33
1967

New BTs -6" D.Fir S.46°E., 6.1 ft. mkd. ¼ S33 CS BT.
7" D.Fir N.70°W., 7.1 ft. mkd. ¼ S28 CS BT.
This corner lies on steep, West slope.