

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 21

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8570)

Set 1/4 sec. post, from which
A B.Oak 12" dia., bears N.55°E., 491 lks.
A W.Oak 14" dia., bears S.65°E., 616 lks.

W. F. Briggs, Co. Surveyor - Wit: James Levens, W.C. Kennedy - July 23, 1900 - Vol. 2 Page 96

Set corner by setting a post from one old BT. Marked trees as follows:
W.Oak 18" dia., bears S.65°E., 616 lks. (Old BT)
B.Oak 8" dia., bears N.54°E., 451 lks. (New BT)

George J. Wenderoth - 1952 - M 8-25 and M 7-53

3/4" Iron pipe.
8" W.Oak bears N.46°35'E., 13.9 ft.
8" W.Oak bears S.8°37'E., 26.5 ft.

Fd. OK, by Rambo, March 1992, M 114-78

BLM Dependent resurvey by Arthur R. Rambo, & Francis Simon Cadastral Surveyors under Group No. 2143, surveyed May 2006/Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21677-8)

The 1/4 sec. cor. of secs. 16 and 21, perpetuated by Wenderoth, in 1952, filed in Survey Nos. M7-53 and M8-25, and utilized by Arthur R. Rambo, in 1992, monumented with an iron pipe, 3/4" dia., firmly set, projecting 4" above the ground, from which remains of an original bearing tree:

An oak stump hole, bears S.65°E., 403.4 ft., with a 24" dia., sawed oak stump lying alongside, no marks visible. (Record, 406.6 ft.)

and bearing trees mkd. by Wenderoth

An oak, 19" dia., bears N.45°E., 14.1 ft., with a healed blaze.

An oak, 17" dia., bears S.10 3/4°E., 26.6 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2 1/2" dia., 27" in the ground, directly over iron pipe, with brass cap mkd.

T 32 S R 5 W

1/4 S 16
S 21

2006

continued next page

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Deposit a magnet in a white plastic case at the base of the stainless steel post.