

PRIMARY CORNER DESCRIPTION No. Sec. cor. for 27 and 28 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 (DCSO records Vol. 20 Page(s) 8597-98)

At the point of intersection, I set a Maple post, 3 ft. long, 4" sq., 24" in the ground for closing cor. of sec. 27 and 28, marked C C T32S R5W on S.; S27 on E.; and S28 on W. faces, with 3 grooves on E. and W. faces, from which

 A Fir 28" dia., bears S.30°E., 53 lks. mkd. T32S R5W S27 BT.

 A Fir 8" dia., bears S.6°W., 14 lks. mkd. T32S R5W S28 BT.

George J. Wenderoth - 1955 - C.S. File 46/148

3/4" Iron pipe.

 12" Maple S.20°E., 52.0 ft.

 14" Maple N.73°30'W., 74.2 ft.

Survey by Richard L. Templin - For: Rogue Valley Trees, Inc. Aug. 10, 1975 - C.S. File 58/64

Found - 3/4" Iron pipe.

 Maple, 13", bears S.20°E., 52.0 ft., scribe visible. The NW tree is down and dead.

New BT - D.Fir 50" bears S.34°E., 35.0 ft. with a partly healed blaze, with many years of overgrowth. I placed a marked location poster on the North side of the tree.

BLM resurvey by Virgil L. Stanger, Cadastral Surveyor, under Group #1145, surveyed May/Aug. 1983 - (DCSO records Vol. 47 Page(s) 17885)

(At 39.705 chs.)

The original closing cor. of secs. 27 and 28, perpetuated and recorded by Wenderoth in 1956, monumented with an iron pipe 3/4" dia., firmly set, projecting 6" above ground, from which the remaining original bearing tree:

 A Fir 56" dia., bears S.32 3/4°E., 53 lks. dist., with illegible scribe marks visible on chopped open blaze. (Rec. S.30°E.)

and the remains of a bearing tree mkd. by Wenderoth:

 A root hole bears S.18 3/4°E., 79 lks. dist., alongside of which is a down Maple 13" dia., with chopped, decayed blaze, no marks visible.

(At 39.72 chs.)

True point for the closing cor. of secs. 27 and 28.

(Cont. Next Page)

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 379300

PRIMARY CORNER DESCRIPTION C.C. for Secs. 27 and 28 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

S 21
S 28 | S 27
T 32 S | R 5 W
C C
1983

from which

A Maple 9" dia., bears S.67¼°E., 106 lks. dist., mkd. T32S R5W S27 CC BT.

A Fir 9" dia., bears S.30¼°W., 23 lks. dist., mkd. T32S R5W S28 CC BT.

(From this point, the cor. of secs. 21 and 22 only, bears S.89°10'E., 1.10 chs. dist.)

Fd. BLM brass cap OK, Jan. 1991, M 112-23

Fd. ok by R. Wytcherly 5/2007 - M153-29