

PRIMARY CORNER DESCRIPTION Sec Cor for 27, 28, 33 and 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 (DCSO records Vol. 20 Page(s) 8594-95)

-----  
Set a Fir post, 3 ft. long, 4" sq., 24" in the ground, for cor.of secs. 27, 28, 33 and 34, marked T32S S27 on NE.; R5W S34 on SE.; S33 on SW.; and S28 on NW. faces; with 1 notch on S. and 3 notches on E. edges, from which  
A Fir 18" dia., bears N.29°E., 63 lks. mkd. T32S R5W S27 BT.  
A Laurel 20" dia., bears S.57°E., 19 lks. mkd. T32S R5W S34 BT.  
A Laurel 5" dia., bears S.89°W., 52 lks. mkd. T32S R5W S33 BT.  
A Fir 40" dia., bears N.10°W., 38 lks. mkd. T32S R5W S28 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - July 1967 - C.S. File 53/52-35

-----  
Found - Orig. 18" now 22" D.Fir, N.29°E., 41.6 ft., faint bark scribing "S W 7".  
Orig. 20" Laurel, now down, S.57°E., 12.5 ft. scribe marks visible but not legible.  
Orig. 40" now 48" D.Fir N.10°W., 25.1 ft., faint bark scribing.  
No trace of SW bearing tree.

Set Brass cap at cor. mkd: County Surveyors Office  
T 32 S R 5 W  
S 28 | S 27  
S 33 | S 34  
1967

New BTs -11" D.Fir S.48°E., 27.8 ft. mkd. T32S R5W S34 CS BT.  
40" D.Fir stump S.27°W., 31.8 ft. mkd. T32S R5W S33 CS BT.  
15" Cedar N.81°W., 49.9 ft. mkd. T32S R5W S28 CS BT.

BLM resurvey by Virgil L. Stanger, Cadastral Surveyor, under Group #1145, surveyed May/Aug. 1983 - (DCSO records Vol. 47 Page(s) 17881)

-----  
The sec. cor., perpetuated and recorded by the County Surveyors Office in 1967, monumented with an iron post, 1" dia., firmly set, projecting 16" above ground with marked brass cap.  
from which the remains of the original bearing trees  
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec cor for 27, 28, 33 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A shattered Fir stump bears N.29°E., 63 lks. dist., with scribe marks 32 BT visible on bark blaze.  
A root hole bears S.57°E., 19 lks. dist., alongside of which is down Madrone, 20" dia., with chopped open blaze, no marks visible.  
A root hole bears N.10°W., 38 lks. dist., alongside of which is a down Fir, 48" dia., no marks visible.  
and the remains of bearing trees mkd. by the County  
A Fir 18" dia., bears S.48½°E., 42 lks. dist., with healed blaze.  
A Fir stump 40" dia., bears S.27½°W., 48 lks. dist., with scribe marks T32S R5W S33 CS BT visible on open blaze.  
and new bearing trees  
A Cedar 8" dia., bears N.41 3/4°E., 63½ lks. dist., mkd. T32S R5W S27 BT.  
The west fork of a twin Cedar, 6" dia., bears N.27¼°W., 72½ lks. dist., mkd. T32S R5W S28 BT.  
Corner is located 70 lks. East and approx. 25 ft. lower in elevation from dirt road, 25 lks. wide, bears N. and S.

Ken Hoffine - For: Lone Rock Timber Co - June 2020 - M177-25  
-----  
Found - 1967 county cap 1.5 feet above ground  
40" D.Fir stump bears S.27½°W., 31.68 ft per BLM  
1983  
32" D.Fir bears S.48½°E 27.55 ft (record 1983 BLM S.48½°E., 27.72 ft) healed face and tag  
17" Cedar bears N.41¼°E., 41.91 ft per 1983 BLM record healed face and tag  
14" Cedar bears N.27¼°W., 47.85 ft per 1983 BLM record healed face and tag  
Corner lies on steep east facing slope approx 100 ft west of paved murphy road. Metal fence post approx 0.5 ft west of corner.