

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 (DCSO records Vol. 20 Page(s) 8598)

Set a Cedar post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S28 on W. and 27 on E. face; from which
A Fir 5" dia., bears N.79°E., 18 lks. mkd. 1/4 S27 BT.
A Fir 45" dia., bears N.72°W., 23 lks. mkd. 1/4 S28 BT.
This point is 60 ft. below ridge.

George J. Wenderoth - Jan. 1956 - C.S. File 42/88

3/4" iron pipe, from which
32" Fir S.84°50'E., 25.7 ft.
16" Fir N.68°10'W., 9.8 ft.

BLM resurvey by Virgil L. Stanger, Cadastral Surveyor, under Group #1145, surveyed May/Aug. 1983 - (DCSO records Vol. 47 Page(s) 17884-85)

The 1/4 sec. cor., perpetuated and recorded by Wenderoth in 1956, from original evidence no longer in existence, monumented with an iron pipe 3/4" dia., firmly set, projecting 6" above ground, from which bearing trees mkd. by Wenderoth:

A Fir 40" dia., bears S.87 1/4°E., 40 1/2 lks. dist., with healed blaze.

A Fir 18" dia., bears N.69°W., 15 1/2 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, directly over iron pipe with brass cap marked

T 32 S R 5 W

1/4

S 28 S 27

1983