

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 21 and 22 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8567)

Set post, cor. to secs. 21, 22, 27 and 28 on steep descent to the N., from which
A Maple 7" dia., bears N.64°W., 41 lks.
A Fir 10" dia., bears N.59°E., 32 lks.
A Chinquapin 6" dia., S.50°E., 45 lks.
A Laurel 12" dia., bears S.19°W., 56 lks.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 (DCSO records Vol. 20 Page(s) 8597)

Intersect E. and W. line, 111 lks. W. of cor. of secs. 21, 22, 27 and 28, which cor. being gone, I reestablish same by setting a Fir post 3 ft. long, 4" sq., 24" in the ground, marked T32S S22 on NE.; R5W S27 on SE.; S28 on SW and S21 on NW. faces, with 2 notches on S. and 3 notches on E. edges; and witnessed as described by the surveyor general, except the NW BT which had fallen and I replaced by
A Maple 5" dia., bears N.13°W., 84 lks. mkd. T32S R5W S21 BT.
I destroy all marks referring to secs. 27 and 28.

George J. Wenderoth - 1955 - C.S. File 46/148

3/4" Iron pipe.
11" Maple N.47°E., 36.0 ft.
9" Maple S.72°30'E., 38.1 ft.

BLM resurvey by Virgil L. Stanger, Cadastral Surveyor, under Group #1145, surveyed May/Aug. 1983 - (DCSO records Vol. 47 Page(s) 17881-82)

The cor. of secs. 21 and 22 only, on the N. bdy. of sec. 27, perpetuated and recorded by Wenderoth in 1956, monumented with an iron pipe 3/4" dia., firmly set, projecting 4" above ground, from which the remains of an original bearing tree
The north fork of a sawed twin Fir stump, 28" dia., bears N.59°E., 34½ lks. dist., with chopped open blaze, no marks visible. (Rec. 32 lks.)
and the remains of a bearing tree mkd. by Thiel:
A root crown, with maple shoots, bears N.13°W., 84 lks. dist., alongside of which is a down maple, 8" dia., no marks visible.
and bearing trees mkd. by Wenderoth:
(Cont. Next Page)

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 21 and 22 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Maple 14" dia., bears N.44°E., 55 lks. dist., with
healed blaze.

A Maple 10" dia., bears S.74 3/4°E., 56 lks. dist., with
healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in
the ground, directly over iron pipe, with brass cap marked

T 32 S R 5 W

S 21 S 22

S 27

1983

from which a new bearing tree

A Fir 6" dia., bears N.31°W., 25½ lks. dist., mkd. T32S
R5W S21 BT.

Corner is located in ravine, drains N.20°W.

Fd. 1983 BLM brass cap OK, Jan. 1991, M 112-23