

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec Cor for 15, 16, 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8567)

Set post cor. to secs. 15, 16, 21 and 22, from which
A B.Oak 11" dia., bears N.58°E., 42 lks.
A W.Oak 10" dia., bears S.52°E., 58 lks.
A B.Oak 10" dia., bears S.75°W., 67 lks.
A Y.Pine 12" dia., bears N.30°W., 45 lks.

George Wenderoth - 1955 - M 7-53

Iron grate.
6" Madrona, N.29°35'W., 20.7 ft.
10" B.Oak S.74°30'W., 47.0 ft.
8" W.Oak S.59°39'E., 56.4 ft.
14" Fir N.67°25'E., 41.8 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - July 1967 - C.S. File 53/52-29

Found - Iron grate at section corner.
6" now 10" Laurel, N.29½°W., 20.7 ft, shows good scar.
10" now 11" B.Oak S.74½°W., 47.0 ft., shows good scar.
8" now 8" W.Oak S.59¼°E., 56.4 ft., scribe visible (CS).
14" Fir now cut, N.67½°E., 41.8 ft., scribe visible (15 CS BT)

Set Brass cap alongside I.Grate mkd: County Surveyors Office

T 32 S R 5 W
S 16 | S 15
S 21 | S 22
1967

New BT - 7" B.Oak N.32°E., 15.2 ft. mkd. T32S R5W S15 CS BT. Corner lies 2.0 ft. West of N-S fence line.

Found OK by R. Wytcherley, June 2002 - M137-46