

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8569)

Set ¼ sec. post, from which
A B.Oak 8" dia., bears S.29°E., 20 lks.
A laurel 10" dia., bears S.70°W., 50 lks.

George J. Wenderoth - July 1952 - M 7 - 53

5/8" Iron bolt, from which
18" B.Oak N.19°30'W., 96.7 ft.
8" Madrona S.64°30'E., 26.2 ft.

Douglas Co. Surveyors Office - John Powell, Frank Jones, Joe Brady, crew - July 1967 - C.S. File 53/52-30

Found - 18" now 20" B.Oak N.19½°W., 96.7 ft., shows good scar.
8" Laurel now cut, S.64½°E., 26.2 ft., scribe visible "CS BT"
5/8" bolt at ¼ corner.
New BT - 14" D.Fir N.13½°E., 10.1 ft. mkd. ¼ S15 CS BT.
This corner lies betw. 2 fences approx. 150.0 ft. E. of dirt road, running North.

Fd. OK, Max Hull, April 1990, M 110-12
Fd. OK, A. Rambo, March 1992, M 114-78
Found OK by R. Wytcherley, June 2002 - M137-46

Kristian DeGroot - For: Wayne Brady - May 2013 - M157-72

Found - A 5/8" bolt with a 1" square head, firmly set, flush with ground by Wenderoth in 1952 per M7-53, from which bearing trees by John Powell, DCSO IN 1967:
A 24" B.Oak bears N.20°15'W., 97.1 ft with a healed blaze. (Rec. N.19½°W., 96.7 ft)
A 28" D.Fir bears N.11°45'E., 10.0 ft with healed blaze. (Rec N.13½°E., 10.1 ft)
And a bearing object not of record:
A axle bears S.62°15'W., 0.35 ft.
LAT: 43°47'24.68789" N. LONG: 123°17'16.81311" W.