

PRIMARY CORNER DESCRIPTION Sec Cor for 3, 4, 9 and 10

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Original - W.H. Byars, under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 20 Page(s) 8586)

 Set post cor. secs. 3, 4, 9 and 10, from which
 A Laurel 8" dia., bears N.60°E., 35 lks.
 A Maple 5" dia., bears S.65°E., 27 lks.
 A Fir 40" dia., bears S.50°W., 30 lks.
 A Laurel 7" dia., bears N.60°W., 12 lks.

GL0 survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 20 Page(s) 8602)

 At the cor. of secs. 3, 4, 9 and 10, which having disappeared, I replace by setting a Fir post, 3 ft. long, 4" sq., 24" in the ground, for sec. cor., marked T32S S3 on NE.; R5W S10 on SE.; S9 on SW.; and S4 on NW. faces with 5 notches on S. and 3 notches on E. edges, and witnessed as described by the surveyor general.

GL0 resurvey by Hans W. Thielsen, under Group #320, Surveyed, Oct./Nov. 1955 - (DCSO records Vol. 28 Page(s) 11798)

 The sec.cor., determined at record bearing and distance from two of the original bearing trees:

A Fir 50" dia., bears S.50°W., 30 lks. dist., with marks S9 BT uncovered.
 A Madrona 10" dia., bears N.60°W., 12 lks. dist., with marks S 4 uncovered.

At the corner point

Set an iron post, 36 ins. long, 2 ins. dia., 30 ins. in the ground, with brass cap marked

T 32	S R 5	W
S 4	S 3	
S 9	S 10	
1955		

from which new bearing trees:

A Fir 24" dia., bears N.71¼°E., 93 lks. dist., marked T32S R5W S3 BT.
 A Fir 9" dia., bears S.36¼°E., 18 lks. dist., marked T32S R5W S10 BT.
 A Fir 18" dia., bears S.72°W., 115 lks. dist., marked T32S R5W S9 BT.
 A Fir 12" dia., bears N.36¼°W., 70 lks. dist., marked T32S R5W S4 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew, July 1967 - C.S. File 53/52-33

----- (Cont. Next Page)

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec Cor for 3, 4, 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Found - 1955 brass cap at corner, properly marked.
19" D.Fir now snag, S.72°W., 75.9 ft., scribe visible.
9" now 11" D.Fir S.36°E., 7.9 ft., shows scar.
12" now 16" D.Fir N.36°W., 46.2 ft., face pitched over.
24" D.Fir down, N.74°E., 61.4 ft.
New BTs -12" D.Fir S.70°W., 77.9 ft. mkd. T32S R5W S9 CS BT.
10" Maple N.14°E., 35.6 ft. mkd. T32S R5W S3 CS BT.

Fd. Ok, G.Lang, Sept. 1995, M 125-7

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2925; Surveyed July/Oct. 2018 - (DCSO records Vol. 59 Page(s) 23754-5)

The cor. of secs 3, 4, 9, & 10, reported by Thielsen in 1955, perpetuated by the Douglas Co Surveyor's Office in 1967; monumented with an iron post, 2" dia., firmly set, projecting 8" above the ground, with brass cap (properly) mkd. from which bearing trees reported by Thielsen

- A fir, 24" dia., bears S.33°E., 12.4 ft., with a healed blaze. (Record, S.36¼°E., 11.9 ft.)
- A fir, 84" dia., bears S.50°W., 24.1 ft., with a healed blaze. (Original) (Record, 19.8 ft.)
- A fir, 30" dia., bears N.37°W., 45.5 ft., with a healed blaze. (Record, N.36¼°W., 46.2 ft.)

and BTs mkd. by the Douglas County Surveyor's Office

- A maple, 15" dia., bears N.12½°E., 35.5 ft., with illegible scribe marks visible on rotted blaze.
- A fir, 31" dia., bears S.67¼°W., 75.5 ft., with a healed blaze.