TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 20 Page(s) 8603)

Set a Cedar post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S4 on W. and 3 on E. face, from which
A Cedar 22" dia., bears S.56°E., 35 lks. mkd. ¼ S3 BT.
A Laurel 8" dia., bears S.62°W., 6 lks. mkd. ¼ S4 BT.
This cor. stands 80 ft. below top of spur.

GLO resurvey by Hans W. Thielsen, under Group #320, Surveyed, Oct./Nov. 1955 - (DCSO records Vol. 28 Page(s) 11799)

The ¼ sec. cor., determined at record bearing and distance from the original bearing trees:
A Cedar 35" dia., bears S.56°E., 35 lks. dist. marked with a healed blaze.
A Madrona 16" dia., bears S.62°W., 6 lks. dist., with marks ¼ S4 uncovered.
At the corner point
Set an iron post, 36" long, 1" dia., 30" in the ground, with brass cap marked

¼
S 4 S 3
1955

from which new bearing trees:
A Cedar 25" dia., bears S.65°E., 96 lks. dist. mkd. ¼ S3 BT.
A Cedar 18" dia., bears N.82°W., 26 lks. dist., marked ¼ S4 BT.

Survey by Howard Johnstone - For: Roseburg Resources Co. - July 8, 1988 - M 106-50

Found - 1955 Cadastral brass cap and iron pipe.
18" Cedar N.82°W., 17.2 ft. Tall stump.
35" Cedar S.56°E., 23.1 ft. Tall stump.
25" Cedar S.65°E., 63.4 ft. scribe visible.
New BT - 5" Fir S.46°W., 55.0 ft.