

PRIMARY CORNER DESCRIPTION Sec Cor for 3 & 4; 33 & 34 of T31-5

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Original - Geo. W. Hyde, under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 19 Page(s) 7883)

 Set post cor. to secs. 3, 4, 33 and 34, from which
 A Fir 6" dia., bears S.43°E., 20 lks. dist.
 A Fir 5" dia., bears N.50°E., 31 lks. dist.
 A Fir 6" dia., bears S.71°W., 14 lks. dist.
 A Fir 9" dia., bears N.52°W., 15 lks. dist.

BLM resurvey by Hans W. Thielsen, under Group #320. Surveyed Oct/Nov. 1955 (DCSO records Vol. 28 Page(s) 11785-86)

 The Sec. cor., monumented with a weathered basalt stone, 12 x 8 x 5 ins., firmly set, with no remaining marks.
 from which the original SE. and NW. bearing trees:

A Fir snag 16" dia., bears S.43°E., 20 lks. dist. with marks BT uncovered.
 A Red Fir 30" dia., bears N.52°W., 15 lks. dist., with marks S 3 uncovered.

At the corner point

Set an iron post 36" long, 2" dia., 30" in the ground, with brass cap marked:

T 31	S R 5 W
S 33	S 34
S 4	S 3
T 32 S	
1955	

from which new bearing trees:

A Red Fir 20" dia., bears N.13¼°E., 58 lks. dist., marked T31S R5W S34 BT.
 A Red Fir 30" dia., bears S.68¼°E., 74 lks. dist., marked T32S R5W S3 BT.
 A Red Fir 35" dia., bears S.34°W., 81 lks. dist., marked T32S R5W S4 BT.
 A Red Fir 33" dia., bears N.66°W., 73 lks. dist., marked T31S R5W S33 BT.

Deposit basalt stone alongside the iron post.

Douglas Co. Surveyors Office - John M. Powell and crew - July 28, 1967 - C.S. File 53/52-45

 Found - U.S. Land Office brass cap, properly marked in 1955.
 20" Fir windfall, N.13¼°E., 38.3 ft. shows good scar
 30" now 33" Fir S.68¼°E., 48.8 ft. shows good scar.
 33" now 35" Fir N.66°W., 48.2 ft. shows good scar.
 No trace of SW BT, lies in skid trail.

New BTs -21" D.Fir N.1°E., 82.4 ft. mkd. T31S R5W S34 CS BT.
 30" D.Fir S.77°W., 46.6 ft. mkd. T32S R5W S4 CS BT.

Cont.

PRIMARY CORNER DESCRIPTION Sec Cor for 3 & 4; 33 & 34 of T31-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Adam DeGroot - For: Silver Butte Timber Co. - Dec. 2019 - M171-74

Found - A 2½" USBLM IP by Thielsen in 1955, firmly set and projecting 4" above ground, with a 3¼" brass cap properly mkd. from which

The remaining 1955 BTs:

A burned 30" D.Fir snag bears S.68°15'E., 49.1 ft - I high stump at 4 ft (S.68°15'E., 74 lks)

A burned 29" D.Fir snag bears N.64°45'W., 48.0 ft - I high stump at 4 ft (N.66°W., 73 lks)

The remaining 1967 BT by DCSO, a burned 30" D.Fir snag bears S.76°30'W., 46.6 ft, I high stump at 4 ft (S.77°W., 46.6 ft)

New RMS- A 5/8"x30" IR W/2" BTS alum cap stamped "RM 1 2019" bears N.82°19'27"E., 57.20 ft

A 5/8"x30" IR W/2" BTS alum. cap stamped "RM 2 2019" bears S.35°49'02"E., 61.04 ft.

A 5/8"x30" IR W/2" BTS alum. cap stamped "RM 3 2019" bears S.88°01'13"W., 57.58 ft

A 5/8"x30" IR W/2" BTS alum. cap stamped "RM 4 2019" bears N.13°47'06"W., 53.01 ft

Note - The entire corner area was fully consumed in the 2019 mile post 97 fire, with no living trees within limits.

Lat: 42°49'34.32577"N Long: 123°17'14.45990"W