

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 20 Page(s) 8584)

Set ¼ sec. post, from which
A Maple 12" dia., bears N.55°E., 36 lks.
A Fir 30" dia., bears S.50°W., 41 lks.

GL0 survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 (DCSO records Vol. 20 Page(s) 8595)

¼ sec. cor. post, which having decayed, I reestablish this ¼ sec. cor. by setting a dogwood post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S 27 on N. and 34 on S. face; from which
A W.Fir 7" dia., bears N.76°W., 23 lks. mkd. ¼ S27 BT.
A Fir 24" dia., bears S.87°E., 51 lks. mkd. ¼ S34 BT.
The old BT had fallen down still showing marks.

Survey by George J. Wenderoth - Jan. 1956 - C.S. Fiel 42/88

1½" iron pipe, from which
28" Fir S.87°E., 33.6 ft.
30" Cedar N.62°45'W., 79.4 ft.

Fd. OK, DCSO, R. Tracy, July 6, 1967 C.S. File 53/52-38

BLM resurvey by Virgil L. Stanger, Cadastral Surveyor, under Group #1145, surveyed May/Aug. 1983 - (DCSO records Vol. 47 Page(s) 17880)

The ¼ sec. cor., perpetuated & recorded by Wenderoth in 1953, monumented with an iron pipe, 1½" dia., firmly set, projecting 2" above ground, from which a BT mkd. by Thiel:
A Fir 31" dia., bears S.86°E., 51 lks. dist., with chopped, healed blaze, no marks visible. (Rec. S.87°E.)
At the corner point
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, with brass cap marked
T 32 S R 5 W
¼ $\frac{S\ 27}{S\ 34}$
1983

from which a new bearing tree
A W.Fir 17" dia., bears N.22¼°W., 48 lks., mkd. ¼ S27 BT
Reset iron pipe alongside iron post.

Fd. ok by R. Wytcherly 5/2007 - M153-29

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Ken Hoffine, Lone Rock Timber Co. - Witness: Gary Angiolet -
4/14/2015 - C.S. File 65/89-21

Found - 1983 BLM cap per Vol. 47 pgs 17880-1
31" fir five ft tall stump with chopped out face
bears S.84¼°E., 34.4 ft. (Rec. S.86°E., 33.66 ft)
19" W.Fir bears N.20½°W., 31.4 ft. (rec. N.22¾°W.,
31.68 ft.) healed face & tag.
New - 26" D.Fir bears S.69¾°W., 11.8 ft. we scribe T32S
R5W ¼ S34 BT and tag tree.
Note - Corner lies approx. 80 ft east of small draw, with
old logging unit to the Northeast. We ran a
random traverse starting at the N¼ corner of
section 34 and running westerly to the Northwest
section corner of section 34 then continuing
southerly to the W¼ of section 34. We blazed,
painted, and tagged true line from the N¼ corner
to the Northwest section corner to the W¼ corner
of section 34

Ken Hoffine - For: Lone Rock Timber Co - June 2020 - M177-25

Found - 1983 BLM BCIP 0.2 ft above ground level.
31" Fir five ft tall stump with chopped out face
bears S.84¼°E., 34.4 ft per Hoffine corner
renewal CS 65/89-21
23" W.Fir bears N.20½°W., 31.4 ft per Hoffine corner
renewal CS 65/89-21 healed face we re-tag tree
18" D.Fir bears S.69¾°W., 11.8 ft per Hoffine corner
renewal CS 65/89-21 healed face we retag tree
Corner lies approx. 80 ft east of small draw, with old
logging unit to the NE.