

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO rec Vol. 20 Pg 8566)

Set ¼ sec. post.
Enter point of Prairie, from which
A W.Oak 24" dia., bears N.40°W., 267 lks.
A Balm, 3" dia., bears S.20°E., 53 lks.

Survey by Gerald D. Riley - March 2, 1972 - C.S. File 55/189

Corner renewed by proportionate measurements.
Set 1½" Iron pipe at ¼ corner.

Douglas Co. Surveyors Office - Stephen Flause, Deputy - T. Plouff, S. Means crew - April 22-23, 1980 - C.S. File 61/6-33

Found - 1½" iron pipe protruding 0.2 ft. from ground, firmly set. Originally set by proportionate measurement. Searched for orig. bearing trees thoroughly, none found.

From Carlile survey, M 48-71, a 5/8" iron rod, firmly set and flush with surface of ground, bears S.89½°E., 703.5 ft. (Rec. S.88°11'14"E., 706.20 ft.)

from this iron rod,
another 5/8" iron rod, firmly set and flush with ground from Riley survey, C.S. 55/189, bears S.37°W., 2.15 ft. Record distance as per M 48-71, 300.0 ft. from car axle to ¼ S15|S22, S.88°11'14"E. We find the dist. to be 278.29 ft.

(See attachments to field notes in C.S. 61/6-33)

New BTs -A 7" Ash bears N.85½°E., 37.9 ft. scribed "¼ S15 CS BT" on a double blaze.

An 8" Ash (most westerly trunk of triple trunk tree) bears S.71½°E., 11.0 ft. (bearing and dist. to center of root crown of triple trunk), scribed "¼ S22 CS BT" on a double blaze.

A 10" Ash (most easterly trunk of triple trunk tree), bears S.73°W., 36.3 ft. (bearing and dist. taken to center of root crown of triple trunk), scribed "¼ S22 CS BT" on a double blaze.

A 12" Ash bears N.29°W., 49.6 ft. scribed "¼ S15 CS BT" on a double blaze.

We tag all trees with DCSO BT tags.

Found OK by R. Wytcherley, June 2002 - M137-46