

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8569)

Set ¼ sec. post on S. side of Butte, from which
A B.Oak 20" dia., bears N.8°E., 162 lks.
A B.Oak 7" dia., bears S.7°E., 26 lks.

Wm. Briggs, Co. Surveyor - For: Geo. Cresey - Sept. 12, 1889 - Vol. 1 Page 139

Set post from one of the original BT and one new BT, from which
A B.Oak 4" dia., bears S.17½°E., 14 lks.

George J. Wenderoth - July 1956 - C.S. File 47/98 and M 5-27

Found - 26" B.Oak N.8°E., 106.9 ft., partly dead.
12" B.Oak S.7°E., 17.2 ft., dead.
Drove a 3/4" Iron pipe at corner point.
Marked - 16" B.Oak S.32°W., 11.3 ft.
18" B.Oak N.57°40'E., 70.2 ft.
(Distance between the corner above and the corner to secs. 9, 10, 15 and 16, is 2692.6 ft., course S.89°34'E.)

Survey by Max H. Hull, L.S. #901 - For: Gregory Forest Products - April 1990 - C.S. File 63/115 and M 110-12

Found - B.Oak 18" dia., S.32°W., 11.3 ft., blaze healed.
B.Oak 20" dia., N.57°40'E., 70.2 ft., blaze healed.
Set 5/8" x 30" iron rod with yellow plastic cap mkd. "HULL RS 901".
New BTs -28" S.Pine N.50°W., 19.3 ft. scribed.
12" Cedar S.25°E., 8.5 ft. scribed.

Fd. Ok, G.Lang, Sept. 1995, M 125-7

Found OK by R. Wytcherley, June 2002 - M137-46