

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 20 Page(s) 8587)

-----  
Set ¼ sec. post, from which  
A Chinquapin 9" dia., bears S.70°E., 8 lks.  
A Chinquapin 10" dia., bears N.30°W., 15 lks.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 20 Page(s) 8625)

-----  
The old post being burned and old bearing trees badly decayed, I reestablish this cor. by setting a Fir post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S3 on N. face and S10 on S. face, from which  
A Fir 22" dia., bears N.9°E., 116 lks. dist., mkd. ¼ S3 BT  
A Fir 36" dia., bears S.10°W., 123 lks. dist., mkd. ¼ S10 BT.  
Cor. stands on W. slope of mountain about 250 ft. above stream.

GLO resurvey by Hans W. Thielsen, under Group #320, Surveyed, Oct./Nov. 1955 - (DCSO records Vol. 28 Page(s) 11798)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 36 ins. long, 1 in. dia., 30 ins. in the ground, with brass cap marked  
$$\frac{1}{4} \frac{S}{S} \frac{3}{10}$$
  
1955

from which  
A Red Fir 25" dia., bears N.13°E., 58 lks. dist., marked ¼ S3 BT.  
A Red Fir 20" dia., bears N.41½°W., 24 lks. dist., marked ¼ S10 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - August 1967 - C.S. File 53/52-5

-----  
Found - 25" now 28" D.Fir N.13°E., 38.3 ft., shows good scar  
20" D.Fir now windfall, S.41½°W., 15.8 ft.  
GLO brass cap, 1955, properly marked.  
New BT - 12" D.Fir S.74°E., 46.0 ft. mkd. ¼ S10 CS BT.  
This corner lies 175.0 ft. West of ridge on West slope.

Fd. Ok, G.Lang, Sept. 1995, M 125-7