

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 474100

PRIMARY CORNER DESCRIPTION C C for Secs. 2 and 3 only, T33-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8970-71)

-----  
At point of intersection for closing cor. on N. bdy. of Tp. 4.90 chs. W. of cor. established for cor. to secs. 34 and 35, T32S R5W, I set a basaltic stone 16 x 8 x 6 ins., 11" in the ground for closing cor. to secs. 2 and 3 marked C C with 2 notches on the E. and 4 notches on W. edges, from which  
A Fir 12" dia., bears S.62°E., 34 lks. dist., marked T33S R5W S2 BT.  
A Matherone (sic) 8" dia., bears S.86°W., 8 lks. dist., marked T33S R5W S3 BT.  
A Fir 8" dia., bears N.70°E., 33 lks. dist., marked T33S R5W C C S2 and 3 BT.

Ben B. Irving, Co. Surveyor - June 1930 - C.S. File 37/23; C.S. File 46/109 and RM 1-11

-----  
A rock 6" x 8" x 6" above ground, original corner as described. O.B.T.s in good condition as follows:  
8" Fir now 12", N.70°E., 33 lks.  
12" Fir, S.62°E., 8 lks.  
8" Madrone now 12", S.68°W., 8 lks. (GL0 notes says S.86°W, V.L.)  
I reblaze and scribe all BTs.

Douglas Co. Surveyors Office - John M. Powell, Joe Brady, crew - August 1967 - C.S. File 53/52-19

-----  
Found - 6x8x6 corner stone marked CC.  
12" now 18" D.Fir N.70°E., 21.8 ft., shows bark scribing, "T32S R5W BT" plus a good original face.  
12" D.Fir now 16" stump, S.62°E., 22.4 ft., shows good bark scribe of "T33S R5W".

Set Brass cap at cor. mkd: County Surveyors Office

T 32 S R 5 W  
C C  
-----  
S 3 | S 2  
1967

(Set brass cap beside cor. stone)  
New BTs -28" D.Fir S.28°W., 31.9 ft. mkd. T33S R5W S3 CC CS BT.  
22" Cedar S.7°E., 49.0 ft. mkd. T33S R5#W S2 CC CS BT.

This corner lies in an old cutting unit on E. slope.

continued next page

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 474100

PRIMARY CORNER DESCRIPTION CC for Secs. 2 and 3 only, T33-5

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Ronald Quimby - For: Plum Creek Timber Co. - July 2015 - M166-36

-----  
Found - 2½" 1967 DCSO brass cap  
17" cedar S.7°E., 49.0' - healed scribe  
30" fir S.39°W., 21.8' - healed scribe, un-recorded  
New BTs- 8" madrone N.20°W., 19.5' scribed "CC S3 BT"  
4" fir N.26°E., 14.7' scribed "CC S2 BT"

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 3006; Surveyed April 2021/Nov. 2022 - (DCSO records Vol. 59 Page(s) 24113-4)

-----  
From this corner (CC of Secs 34 & 35 T32-5) The closing cor. of secs. 2 and 3, perpetuated by Irving, Douglas County Deputy Surveyor, in 1930; subsequently perpetuated by the Douglas County Surveyor's Office in 1967; and further perpetuated by Quimby, in 2015; bears S.89°40'48"W. 334.18 ft.; monumented with an iron post, 1½" dia., firmly set, projecting 16" above the ground, in a collar of stone, with brass cap (properly) mkd.

from which the remains of an original bearing tree  
A fir stump, 21" dia., bears N.70°E., 21.8 ft., with a healed blaze. This tree was mkd. again by Irving in 1930.

and BTs mkd. by the Douglas County Surveyor's Office  
A cedar, 19" dia., bears S.18½°E., 48.3 ft., with scribe mark 3S 5W visible on partially healed blaze.

A fir, 30" dia., bears S.37¼°W., 21.5 ft., with a healed blaze.

and bearing trees mkd. by Quimby  
A fir, 5" dia., bears N.27¼°E., 14.5 ft., with a healed blaze.

A madrone, 8" dia., bears N.19½°W., 19.0 ft., with illegible scribe marks visible on partially healed blaze.