TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8563-64)

Set ¼ sec. post, from which
A B.Oak 12" dia., bears S.80°W., 19 lks.
A B.Oak 18" dia., bears S.52°E., 18 lks.
(Monott's house bears S.41°W.)

George J. Wenderoth - For: Donald W. Brady - May 1968 - M 35-79

Set Brass cap, from which
46" B.Oak N.16°20'E., 14.4 ft., scribed.
16" Fir stump, S.55°33'W., 17.0 ft. scribed.
Affidavit to be added.

Fd. Ok, G.Lang, Sept. 1995, M 125-7
Found OK by R. Wytcherley, June 2002 - M137-46

Kristian DeGroot - For: Wayne Brady - May 2013 - M157-72

Found - A 1¼" iron pipe by Wenderoth in 1968 per M35-79, firmly set, projecting 12" above the ground with a 2½" brass cap marked:
COUNTY SURVEYORS OFFICE
1/4 COR
15+14
LS 5
From which bearing trees by Wenderoth in 1968:
A 48" B.Oak bears N.15°15E., 15.6 ft (14.2 ft to face) with healed blaze (Rec. N.16°20'E. 14.4 ft)
A 16" D.Fir low cut stump bears S.54°15'W., 17.0 ft. (Rec. S.55°33'W., 17.0 ft)
New BT - A 13" D.Fir bears N.76°30'W., 39.5 ft, scribed "¼ S15 BT".
LAT: 42°47'24.371828" N. LONG: 123°16'05.41312" W.

Fd. as per record 11/2023 R Brown - M178-77