

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8564)

Set post, cor. to secs. 10, 11, 14, & 15, from which,
A Fir, 24" dia., bears S.62°E., 19 lks.
A Dogwood, 3" dia., bears S.39°W., 44 lks.
A Cedar, 22" dia., bears N.46°W., 65 lks.
A Fir, 10" dia., bears N.62°E., 64 lks.

Greg Lang - For: Silver Butte Timber Co. Sept. - 1995 - M 125-7

Set - 5/8"x30" I.R. w/plastic cap mkd: "LANG SURVEYING"
Spike in face of 12¼" Fir, bears S.56°E., 17.65' scribed S14 BT"
Spike in face of 8½" Fir, bears S.9°14"W., 35.27' scribed S15 BT"
Spike in face of 11 3/4" Madrone, bears N.72°30'W., 31.22' scribed S10 BT"
Spike in face of 11" Fir, bears N.31°51'E., 41.85' scribed S11 BT"

Found OK by R. Wytcherley, June 2002 - M137-46
Fd. 2007 BLM brass cap & BTs by R. Wytcherley, 5/2007 M153-28 (BLM resurvey not approved at this time)

BLM Dependent resurvey by Arthur R. Rambo, & Francis Simon Cadastral Surveyors under Group No. 2143, surveyed May 2006/Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21673-4)

The cor. of secs. 10, 11, 14, and 15, reestablished by proportionate measurement by Lang, in 1995. There is no remaining evidence of the original cor., therefore this position is accepted as the cor.; monumented with an iron rod, 5/8" diam., firmly set, projecting 2" above the ground, with a yellow plastic cap mkd. LANG SURVEYING, from which bearing trees mkd. by Lang:

- A fir, 11" dia., bears N.32°E., 42.5 ft., with a healed double blaze.
- A fir, 19" dia., bears S.56°E., 17.8 ft., with a healed double blaze.
- A fir, 12" dia., bears S.9°W., 35.8 ft., with a healed double blaze.
- A madrone, 16" dia., bears N.72¾°W., 31.3 ft., with scribe marks S10 visible on partially healed double blaze.

At the corner point continued next page

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, directly over the iron rod, with brass cap mkd.

T 32 S R 5 W

S 10 | S 11

S 15 | S 14

2007

Deposit a magnet in a white plastic case at the base of the stainless steel post.