

PRIMARY CORNER DESCRIPTION Sec cor for 2, 3, 10 and 11

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8565)

-----  
Set post, cor. to secs. 2, 3, 10 and 11, on NE. slope, from which

- A Willow 2" dia., bears S.50°W., 25 lks.
- A Laurel 5" dia., bears S.43°E., 39 lks.
- A Laurel 6" dia., bears N.56°E., 86 lks.
- A Laurel 9" dia., bears N.36°W., 33 lks.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 (DCSO records Vol 20 Pages 8625-26)

-----  
The old post being gone and old bearing trees badly decayed, I reestablish this cor. by setting a Fir post, 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 2, 3, 10 and 11, marked T32S S2 on NE.; R5W S11 on SE.; S10 on SW.; and S3 on NW.; with 5 on S. and 2 on E. faces, from which

- A Laurel 12" dia., bears N.36°E., 26 lks. marked T32S R5W S2 BT.
- A Laurel 7" dia., bears S.66°E., 16 lks. marked T32S R5W S11 BT.
- A Fir 6" dia., bears S.69°W., 59 lks. marked T32S R5W S10 BT.
- A Laurel 10" dia., bears N.42°W., 19 lks. marked T32S R5W S3 BT.

George J. Wenderoth - August 1952 - C.S. File 45/98

-----  
Set 3/4" iron pipe.

- 30" W.Fir S.34°15'E., 36.0 ft.
- 34" Fir S.86°45'E., 32.0 ft.
- 16" Fir N.68°20'E., 62.8 ft.
- 28" Fir N.31°30'W., 35.0 ft.

Corner OK, DCSO, John Powell, August 1967 C.S. 53/52-6

Cadastral survey by Hans W. Thielsen under Group # 320. Surveyed, Oct./Nov. 1955 (DCSO records Vol. 28 Page(s) 11796)

-----  
The sec. cor., perpetuated by an iron pipe, 1" dia., 10" above ground, set by the County in 1952.

from which bearing trees marked by the County:

- A Fir 16" dia., bears N.68¼°E., 95 lks. mkd. S2 CS BT.
- A Fir 32" dia., bears S.86°45'E., 48 lks. mkd. S11 CS BT

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 2, 3, 10 and 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

A Fir 30" dia., bears S.34¼°W., 55 lks. mkd. S10 CS BT.  
 A Fir 28" dia., bears N.31½°W., 54 lks. mkd. S3 CS BT.  
 At the corner point  
 Set an iron post, 36" long, 2" dia., 30" in the ground, with  
 brass cap marked

|              |      |
|--------------|------|
| T 32 S R 5 W |      |
| S 3          | S 2  |
| S 10         | S 11 |
| 1955         |      |

from which new bearing trees  
 A Red Fir 14" dia., bears N.56°E., 123 lks. dist., marked  
 T32S R5W S2 BT.  
 A Red Fir 24" dia., bears S.29°E., 96 lks. dist., marked  
 T32S R5W S11 BT.  
 A W.Fir 16" dia., bears S.35°W., 172 lks. dist., marked  
 T32S R5W S10 BT.  
 A Red Fir 50" dia., bears N.54½°W., 132 lks. dist., marked  
 T32S R5W S3 BT.  
 Reset pipe alongside the iron post.

Greg Lang - For: Silver Butte Timber Co. Sept. - 1995 - M  
 125-7

-----  
Corner Report only

Found - Brass cap  
 7" Hem. bears S.5°W., 14 lks.  
 39" Fir bears S.86°45'E., 32.0'  
 30½" Fir bears S.83°E., 63'  
 26" Fir bears N.68°20'E., 62.8'  
 29 3/4" Fir bears N.31°30'W., 35.0'  
 53¼" Fir bears N.55°W., 80'  
 26" Fir bears N.63°E., 81'

BLM Resurvey, by Francis J. Simon, Cadastral Surveyor, under  
 Group No. 1733. Surveyed May thru Nov. 1994. (D.C.S.O.  
 records Vol. 52 Page(s) 19685)

-----  
 The cor. of secs. 2, 3, 10, and 11, monumented with an iron  
 post, 2 ins. diam., firmly set, projecting 6 ins. above the  
 ground, with brass cap mkd.

|          |      |
|----------|------|
| T32S R5W |      |
| S 3      | S 2  |
| S 10     | S 11 |
| 1955     |      |

from which the remains of trees mkd. by the County  
 Surveyor's Office in 1952  
 (Cont. Next page)

PRIMARY CORNER DESCRIPTION Cor Secs 2, 3, 10, & 11

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

A fir, 26" dia., bears N.69¼°E., 95 lks., with healed blaze. (Record, N.68¼°E.)  
A fir, 39" dia., bears S.86¾°E., 50½ lks., with healed blaze. (Record, 48 lks.)  
A fir, 29" dia. bears N.31½°W., 54 lks with healed blaze and the remains of trees mkd. by Thielsen  
A red fir, 25" dia. bears N.56°E., 120½ lks. with healed blaze.  
A red fir, 30" dia., bears S.82¾°E., 96 lks. with healed blaze. (Record, S.29°E.)  
and a new tree  
A hemlock, 7" dia., bears S.5°W., 14 lks., mkd. T32S R5W S10 BT.  
The iron pipe set by the County Surveyor's Office, 1 in. diam., firmly set, projecting 10 ins. above the ground, is alongside the iron post.

Fd. Ok by M. Heimbürger, May 2005 - M148-24

BLM Dependent resurvey by Arthur R. Rambo, & Francis Simon Cadastral Surveyors under Group No. 2143, surveyed May 2006/Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21675-6)  
-----  
The cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2" dia., firmly set, projecting 9" above the ground, with brass cap (properly) mkd.  
from which bearing trees mkd. by the Douglas County Surveyor's Office, reported by Simon in 1994  
A fir, 30" dia. bears N.69¼°E. 62.7 ft with a healed blaze  
A fir, 43" dia. bears S.86¾°E. 33.3 ft with a healed blaze  
A fir, 32" dia. bears N.31½°W. 35.6 ft with a healed blaze  
and bearing trees mkd. by Thielsen, reported by Simon in 1994  
A fir, 30" dia. bears N.56°E., 79.5 ft with a healed blaze  
A fir, 34" dia. bears S.82¾°E. 63.4 ft with a healed blaze  
and a bearing tree mkd. by Thielsen  
A fir, 56" dia., bears N.54½°W., 80.2 ft., with a healed blaze. (Record, 87.1 ft.)  
and a bearing tree mkd. by Simon in 1994  
A hemlock, 10" dia bears S.5°W. 9.2 ft with a healed blaze  
The iron pipe set by the Douglas County Surveyor's Office, 1" dia., firmly set, projecting 17" above the ground, is alongside the iron post.