

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 20 Page(s) 8585)

Set 1/4 sec. post, from which
A Cedar 24" dia., bears West, 36 lks.
A Fir 40" dia., bears N.70°E., 34 lks.

GLO resurvey by Hans W. Thielsen, under Group #320, Surveyed, Oct./Nov. 1955 - (DCSO records Vol. 28 Page(s) 11797)

The 1/4 sec. cor., determined at record bearing and distance from the remaining original bearing tree:

A Cedar 28" dia., bears West, 36 lks. dist., with marks 1/4 S uncovered.

At the corner point

Set an iron post 36" long, 1" dia., 30" in the ground, with brass cap marked:

1/4
S 3|S 2
1955

from which new bearing trees:

A Cedar 28" dia., bears N.38°E., 48 lks. dist., marked 1/4 S2 BT.

A Cedar 40" dia., bears N.37°W., 66 lks. dist., marked 1/4 S3 BT.

Fd. Ok by M. Heimbürger, May 2005 - M148-24