

PRIMARY CORNER DESCRIPTION Center W. 1/16 cor. for Sec. 11

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Survey by W. F. Briggs, - For: G. B. Johns and Sons - July 31, 1900 - Vol. 2 Pg. 99

Set Fir post, from which
B.Oak 20" dia., bears S.54½°W., 5 lks.
B.Oak 10" dia., bears N.78½°E., 19 lks.

George J. Wenderoth - August 1952 - C.S. File 45/98

Found 1" Iron bar
20" B.Oak N.78°30'E., 12.8 ft.
16" Fir N.10°30'E., 9.4 ft.
16" Fir N.54°30'W., 14.8 ft.

BLM Dependent resurvey by Arthur R. Rambo, & Francis Simon Cadastral Surveyors under Group No. 2143, surveyed May 2006/Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21696-7

The center W 1/16 sec. cor., established by the Douglas County Surveyor's Office in 1900, filed in Volume 2, page 99, and perpetuated by the Douglas County Surveyor's Office in 1909 and 1952, both filed in 1952 in C.S. No 45/98, utilized by F. Neil Hibbs, in 2006, filed in Survey No. M146-35, and is accepted as the cor.; monumented with an iron pipe, 1" dia., firmly set, projecting 1" above the ground, from which the remains of bearing trees reported by the Douglas County Surveyor's Office in 1952:

A fir, 26" dia., bears N.9¾°E., 10.4 ft., with a healed blaze.

A root hole, bears N.54½°W., 14.8 ft., with down decayed fir alongside, size indeterminate, no marks visible.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over iron pipe, with brass cap mkd.

C ^{W 1/16} C
S 11
2007

from which a new bearing tree

A madrone, 10" dia., bears N.88½°W., 28.2 ft., mkd. CW1/16 S11 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.