

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 20 Page(s) 8580)

Set ¼ sec. post, from which
A Laurel 24" dia., bears N.70°E., 22 lks.
A Pine 36" dia., bears S.10°E., 52 lks.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 (DCSO records Vol. 20 Page(s) 8614)

The ¼ sec. cor.; the post having disappeared, I set a Laurel post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S26 on N. face, and 35 on S. face, from which
A Laurel 24" dia., bears N.70°E., 22 lks. mkd. ¼ S26 BT.
The original BT.
A Y.Pine 40" dia., bears S.24°W., 133 lks. mkd. ¼ S35 BT.
New bearing tree.
This cor. stands 225 ft. above creek.

George J. Wenderoth - 1953 - C.S. File 45/227; M 5-28 and C.S. file 45/54

Set 1½" iron pipe.
8" Chinquapin N.24°30'W., 11.4 ft.
30" B.Oak S.53°30'E., 68.3 ft.

Fd. OK, by W. Rogers, Jan. 1981, M 87-17

Fd. OK by Raymond Brown, L.S. #2391 - For: Dan Folliad & Jamine Graf Dec. 1994 M 121-50.

Fd. 1½" IP per rec by R. Brown 2/2018 - M171-40
Fd. 1½" IP per rec by R. Brown 7/2019 - M171-65