

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 540240

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by W.F. Briggs, Co. Surveyor - For: John Haight and others - July 30, 1900 - Vol. 2 Page 98

Set Fir Post as per regulation, from which
Fir 24" dia., bears N.46°W., 12 lks.
Fir 30" dia., bears S.42½°E., 73 lks.

W. F. Briggs, Co. Surveyor - For: James Burch - Jan. 14, 1902 - Vol. 2 Page 114

Set post in center of sec. 26 - CS - from which
A Yellow Pine 36" dia., bears N.79°E., 365 lks.
A Fir 30" dia., bears S.66°30'W., 245 lks.

Survey by George J. Wenderoth - 1945 - 1956 - C.S. File 43/24; M 27-11 and C.S. file 45/227

Set Car axle for center of section 26
Found both original BTs
30" Fir S.66°30'W., 161.7 ft. in good shape.
36" Pine N.79°E., 240.9 ft., poor condition.
Mark:
14" Madrone N.42°W., 179.5 ft.

Fd. OK, June 1965, DCSO, Geo. Wenderoth, Deputy, C.S. File 54/5-2

Fd. car axle per rec by R. Brown 2/2018 - M171-40
Fd. car axle per rec by R. Brown 7/2019 - M171-65