

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 540340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 23

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Survey by George J. Wenderoth - June 1957 - C.S. File 45/154

1" Iron pipe.
32" Cedar N.2°W., 66.4 ft.
24" Fir N.76°15'W., 51.8 ft.

Cor. Fd. OK, DCSO, John Powell, Aug. 1967

BLM resurvey by Virgil L. Stanger, Cadastral Surveyor, under Group #1145, surveyed May/Aug. 1983 - (DCSO records Vol. 47 Page(s) 17887)

Point for the center ¼ sec. cor. of sec. 23, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 23 ins. in the ground, with brass cap marked
T 32 S R 5 W
C ¼ S 23
1983

from which

- A Fir 18" dia., bears S.77 3/4°E., 34½ lks. dist., mkd. C ¼ S23 BT.
- A Fir 13" dia., bears N.20 3/4°W., 36½ lks. dist., mkd. C ¼ S23 BT.

From this point, a corner established by G. Wenderoth in 1953, bears N.75°48'E., 0.155 chs. dist., monumented with an iron pipe, 1" dia., firmly set, projecting 4" above ground, from which bearing trees mkd. by Wenderoth:

- A Fir 26" dia., bears N.78°E., 78½ lks. dist., with healed blaze.
- A Cedar 32" dia., bears N.2°W., 102 lks. dist. with healed blaze.

Found OK by D. Edwards, Oct. 2003 - M143-13