

PRIMARY CORNER DESCRIPTION Center ¼ Cor. for Sec. 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Survey by W. F. Briggs, For: G.B. Johns and Sons - July 31, 1900 - Vol. 2 Pg. 99

-----  
Set Fir post.

BLM Dependent resurvey by Arthur R. Rambo, & Francis Simon Cadastral Surveyors under Group No. 2143, surveyed May 2006/Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21694)

-----  
Point for the center ¼ sec. cor. of sec. 11, at intersection with the E. and W. centerline.

Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, with brass cap mkd.

T32S R5W  
C ¼ S 11  
2007

from which

A ponderosa pine, 8" dia., bears S.27½°W., 28.4 ft., mkd. X at breast height and BT at the base.

A ponderosa pine, 11" dia., bears N.80°W., 24.3 ft., mkd. C¼ S11 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Fd. 2007 BLM brass cap & BTs by R. Wytcherley, 5/2007 M153-28

Ron Quimby - Crew: R Vincent & R Heichel - 7/2018 - C.S. File 65/101-55

-----  
Found - BLM brass cap (properly marked)

14" Pine N.80°W., 24.3 ft. good scar.

10" Pine S.27½°W., 28.4 ft. good scar.

New - 16" cedar N.8°W., 33.9 ft. scribed C ¼ S11 BT

18" fir S.88°E., 49.3 ft. scribed C ¼ S11 BT

Note - Compass decl. 15½°E.

Fd. As per record by M. Heimburger 9/2020 - M178-15A-C