

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 540640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Hans W. Thielsen, under Group #320, Surveyed, Oct./Nov. 1955 - (DCSO records Vol. 28 Page(s) 11800)

Point for the center ¼ sec. cor. of sec. 2, at intersection with the E. and W. center line.

Set an iron post, 36 ins. long, 1 in. dia., 30 ins. in the ground, with brass cap marked C ¼ S 2
1955

from which

A Red Fir 31" dia., bears S.37°E., 4 lks. dist., marked C ¼ S2 BT.

A Red Fir 18" dia., bears S.59°W., 8 lks. dist., marked C ¼ S2 BT.

Fd. by G.Nygren 8/2000 M135-46

Fd. Ok by M. Heimburger, May 2005 - M148-24

Ron Quimby - For: Swanson Group - 9/2018 - M174-61

Found - USGLO brass cap per 1955 USBLM Dependant Resurvey
45" R.Fir bears S.37°E., 2.64' [4 lks] w/ healed scribe

38" R.Fir bears S.59°W., 5.28' [8 lks] w/ healed scribe

New BTs- 6" D.Fir bears N.29°W., 21.7' scribed "X"

10" D.Fir bears N.34°E., 31.1' scribed "C ¼ S2 BT"