

PRIMARY CORNER DESCRIPTION East W.P. to 1/4 Cor. Secs. 2 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Resurvey, by Francis J. Simon, Cadastral Surveyor, under Group No. 1733. Surveyed May thru Nov. 1994. (D.C.S.O. records Vol. 52 Page(s) 19683-84)

At the point for the 1/4 sec. cor. of secs. 2 and 11, determined by the irregular boundary method. This point falls in the southbound lanes of Interstate Highway No. 5, and is unsuitable for monumentation. There is no evidence of the 1955 remonumentation of the original corner.

At 6.30 chains east of the 1/4 corner: Point for a witness point on line bet. secs. 2 and 11.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

WP
S 2
S 11
1994

from which

A cedar, 6" dia., bears N.46½°E., 32½ lks., mkd. X BT.

A cedar, 6" dia., bears S.16¼°E., 13 lks., mkd. X BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Witness point is located in a woven wire fence with three strands of barbed wire on top, bears N.40°W. and S.40°E. From this point, control station "EDGE," at latitude 42°49'03.330" N. and longitude 123°15'36.396" W. (NAD 1927), established by the Oregon State Department of Transportation in 1962, bears N. 30°41'53"W., 36.903 chs. dist. (mean bearing and sea level distance); monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, set in concrete, with brass cap mkd. OREGON STATE HIGHWAY DEPT 1962 ELEV STATION EDGE _____ USC&GS DO NOT DISTURB and a triangle.

Fd. Ok by M. Heimbürger, May 2005 - M148-24

BLM Dependent resurvey by Arthur R. Rambo, & Francis Simon Cadastral Surveyors under Group No. 2143, surveyed May 2006/Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21695)

Point for the ¼ sec. cor. of secs. 2 and 11, determined at record bearing and distance from the 1994 witness points. Point falls in the southbound lane of Interstate Highway No. 5. No permanent monument set.

From this point, the witness point in the easterly direction, bears S.89°34'00" E., 415.80 ft., monumented with a stainless steel post, 2½" dia., firmly set, projecting 6" cont.

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 546600

PRIMARY CORNER DESCRIPTION East W.P. to 1/4 Cor. Secs. 2 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

above the ground, with brass cap mkd. WP S2 S11 1994 and a horizontal line, from which bearing trees mkd. by Simon in 1994:

- A cedar, 7" dia., bears N.46½°E., 21.5 ft., with illegible scribe marks visible on a partially healed double blaze.
- A cedar, 8" dia., bears S.16¼°E., 8.6 ft., with illegible scribe marks visible on a partially healed double blaze.

Fd. As per record by M. Heimburger 9/2020 - M178-15A-C