

PRIMARY CORNER DESCRIPTION A.P. on bdy. Sec. 35; & 1 of T33-5

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Butler Ives and George W. Hyde, under Contract #39, dated January 4, 1854 - (DCSO records Vol. 20 Page(s) 8547)

-
- Set post cor. of secs. 35, 36, 1 and 2, from which
- A Y.Pine 20" dia., bears N.61°W., 125 lks.
 - A Y.Pine 16" dia., bears N.51°E., 71 lks.
 - A Y.Pine 20" dia., bears S.47½°E., 102 lks.
 - A Y.Pine 24" dia., bears S.47°W., 105 lks.

GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8957-58)

-
- The cor. to secs. 35 and 36, T32S R5W which is a post greatly decayed and in its place, reset a basaltic stone 12x10x6 ins., 8" in the ground for cor. to secs. 35 and 36 T32S R5W marked with 5 notches on W and 1 notch on E. edges from which the NE bearing tree having fallen down and decayed, I remarked a
- Yellow Pine 30" dia., bears N.70°E., 36 lks. dist., marked T32S R5W S36 BT.
 - A Y.Pine 20" dia., bears S.47°30'E., 102 lks. dist., with well defined blazes partly burnt out which I remarked T33S R5W S1 BT.
 - A Y.Pine 24" dia., bears S.47°W., 105 lks. dist., with well defined blazes.
 - A Y.Pine 20" dia., bears N.61°W., 125 lks. dist., with well defined blazes.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 20 Page(s) 8592)

-
- The Sec. cor. which is a sandstone 8x6x5 ins., above ground, marked with a notch on E. and 5 notches on W. edges, witnessed as described by the surveyor general, except
- A Y.Pine 16" dia., bears N.51°E., 41 lks. mkd. T32S R5W S36 BT.
- The distance given by the surveyor general being 71 lks.
- A Y.Pine, 40" dia., and marked with 2 notches on E. and W. sides, mentioned in the field notes, furnished by the surveyor general, stands W. from closing cor. 251 lks.
- I destroyed all marks referring to secs. 35 and 36

(Cont. Next Page)

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 574100

PRIMARY CORNER DESCRIPTION A.P. on bdy. Sec. 35; and 2, T33-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Joseph Gawron; John Jelley; Rollin Aanrud, Cadastral surveyors, under Group #'s 350 and 566, surveyed, March 1965/Dec. 1967 (DCSO records Vol. 34 Page(s) 13974-75)

The Ives and Hyde standard cor. of secs. 1, 2, 35 and 36, rehabilitated by Sharp in 1894, determined at record distance from the remains of the original bearing trees. This corner now becomes an angle point of sections 1 and 35.

from which the original bearing trees

A burned and rotted Pine stump, size indeterminate bears N.55°E., 71 lks. dist., no marks visible. (Record bearing, N.51°E.)

A burned and rotted Pine stump, size indeterminate bears S.43°E., 102 lks. dist., mkd. BT on a pitch sliver. This tree remarked by Sharp in 1894. (Rec. bearing S.47½°E.)

A burned and rotted pine stump, size indeterminate, bears S.47°W., 105 lks. dist., no marks visible.

A sawed ponderosa Pine stump 40" dia., bears N.61°W., 125 lks. dist., mkd. S35 BT on opened blaze.

and a bearing tree mkd. by Sharp

A Ponderosa Pine 36" dia., bears N.77°E., 36 lks. dist., mkd. S36 BT on a partially healed blaze. (Record bearing, N.70°E.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 28 ins. in the ground, with brass cap marked AP

T 32 S R 5 W
S 35
 \
 S 1
T 33 S
1965

from which

A D.Fir 12" dia., bears N.49°E., 65 lks. dist., mkd. AP T32S R5W S35 BT.

An Incense Cedar 10" dia., bears S.51°E., 52 lks. dist., mkd. AP T33S R5W S1 BT.

The angle point is located on the East edge of an unimproved road, bears N.15°W. and S.15°E.

Fd. Ok by Ron Quimby, 11/2006 - 2006-0105A&B