

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION So. Sec. Cor. for 35 and 36 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 20 Page(s) 8592-93)

-----  
I set a Fir post, 3 ft. long, 4" sq., 24" in the ground for closing corner of secs. 35 and 36, marked C C T32S R5W on N.; S36 on E.; and S35 on W. faces, with 1 groove on E. and 5 grooves on W. faces, from which

A Fir 36" dia., bears N.21°E., 60 lks. mkd. T32S R5W S36 BT.

A Y.Pine 40" dia., bears N.81°W., 58 lks. mkd. T32S R5W S35 BT.

Douglas Co. Surveyors Office - John M. Powell, Joe Brady, crew - August 1967 - C.S. File 53/52-17

-----  
Found - 16" now 34" D.Fir N.21°E., 39.6 ft. Tree had been opened, scribe visible, "T32S".

40" now 45" Pine N.81°W., 38.3 ft.

Set Brass cap at cor. mkd: County Surveyors Office

T 32 S R 5 W  
C C S 35 | S 36  
S 1  
1967

New BTs -9" Laurel N.31°W., 8.3 ft. mkd. CC T32S R5W S35 CS BT.

11" D.Fir N.17°E., 8.3 ft. mkd. CC T32S R5W S36 CS BT.

This corner lies East of A.P., 1965, 351.7 ft.

Corner Fd. and used in BLM survey by Gawron, Jolley and Aanrud, under Group #'s 350 and 566, surveyed, March 1965/Dec. 1967 (DCSO records, Vol. 34 Page 13974)

Fd. OK, by L.D. Smith, May 14, 1982, M 92-34

Fd. OK, by D. Bentz, Aug. 1993, Land Partition 1993-0078

J. McIntosh, survey for State of Oregon Dept. of Forestry May 2000 - M135-1

-----  
Found OK as above, rewitnessed:

Set- orange carsonite markers cbm-250 labeled witness post bears, N.46°E., 2.7 ft. to base.  
bears, N.57°W., 2.7 ft. to base.