

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias	Description

Original - W.H. Byars, under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 20 Page(s) 8580-81)

Set post cor. to secs. 25, 26, 35 and 36, from which
A Live Oak 8" dia., bears N.30°E., 33 lks.
A Live Oak 6" dia., bears S.70°E., 10 lks.
A Live Oak 6" dia., bears S.75°W., 22 lks.
A Live Oak 6" dia., bears N.22°W., 23 lks.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 (DCSO records Vol. 20 Page(s) 8590)

The Sec. cor., which being gone, I reestablish by setting a slate rock 18x16x4 ins., 12" in the ground for cor. of secs. 25, 26, 35 and 36, marked with 1 notch on S. and E. edges, from which
A Live Oak 10" dia., bears N.30°E., 33 lks. mkd. T32S R5W S25 BT.
A Live Oak 8" dia., bears S.70°E., 10 lks. mkd. T32S R5W S36 BT.
A Live Oak 8" dia., bears S.75°W., 22 lks. mkd. T32S R5W S35 BT.
A Live Oak 8" dia., bears N.22°W., 23 lks. mkd. T32S R5W S26 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone, crew - June 1964 - C.S. File 53/52-61

Found - Live Oak now 12" dia., S.70°E., 6.6 ft. Scribing visible on partly exposed face.
Live Oak now 9" dia., S.75°W., 14.5 ft. Faint scars visible.
Live Oak now 12" dia., N.22°W., 15.2 ft. Faint scars visible.
Live Oak now 20" dia., N.30°E., 21.8 ft. Faint scars visible.

All distances are slope distance.
Set 3/4" Iron rod.
Rescribed:
20" Live Oak N.30°E., 21.8 ft. (slope dist.) mkd. "S25 CS BT"
9" Live Oak S.75°W., 14.5 ft. (slope dist.) mkd. "S35 CS BT"
12" Live Oak N.22°W., 15.2 ft. (slope dist.) mkd. "S26 CS BT"
Did not rescribe SE BT.
Corner lies on very steep SW slope.

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

J. McIntosh, survey for State of Oregon Dept. of Forestry
May 2000 - M135-1

Found OK as above, re-witnessed:

Set- orange carsonite markers cbm-250 labeled witness post
bears, S.32°E., 3.1 ft. to base.
bears, S.70°W., 3.2 ft. to base.
