

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 20 Page(s) 8581)

Set ¼ sec.post, from which
A Fir 10" dia., bears N.28°W., 22 lks.
A Laurel 8" dia., bears S.58°E., 26 lks.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 (DCSO records Vol. 20 Page(s) 8613)

The ¼ sec. cor., which having disappeared, I set a cedar post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec.cor., marked ¼ S 26 on W. face, and 25 on E. face, from which
A Fir 15" dia., bears S.53°E., 49 lks. mkd. ¼ S25 BT. (new bearing tree)
A Fir 12" dia., bears N.28°W., 22 lks. mkd. ¼ S26 BT. (original bearing tree)

George J. Wenderoth - 1953 - C.S. File 45/227 and M 5-28

1" Iron pipe.
18" Fir N.28°W., 14.5 ft.
24" Fir S.64°14'E., 66.6 ft.