

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 20 Page(s) 8581)

Set post, cor. to secs. 23, 24, 25 and 26, from which
A Laurel 5" dia., bears N.88°E., 19 lks.
A Laurel 6" dia., bears S.30°E., 75 lks.
A Fir 36" dia., bears S.80°W., 47 lks.
A Laurel 5" dia., bears N.35°W., 20 lks.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 (DCSO records Vol. 20 Page(s) 8613)

The Sec. cor., which having disappeared, I replace by setting a Fir post, 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 23, 24, 25 and 26, marked T32S S24 on NE.; R5W S25 on SE.; S26 on SW.; and S23 on NW. faces, with 2 notches on S. and 1 notch on E. edges, from which
A Fir 7" dia., bears N.16°E., 30 lks. mkd. T32S R5W S24 BT. (New BT.)
A B.Oak 4" dia., bears S.60°E., 39 lks. mkd. T32S R5W S25 BT. (New BT)
A Laurel 8" dia., bear S.51°W., 81 lks. mkd. T32S R5W S26 BT. (New BT)
The BT of Sec. 23 still standing as described by the Surveyor General.

George J. Wenderoth - 1953 and June 1957 - C.S. File 45/227 and M 5-28

3/4" Iron pipe.
30" Fir N.16°E., 19.8 ft.
14" Fir S.69°34'E., 9.0 ft.
14" Fir S.18°20'W., 42.5 ft.
12" Fir N.74°W., 55.3 ft.

BLM resurvey by Virgil L. Stanger, Cadastral Surveyor, under Group #1145, surveyed May/Aug. 1983 (DCSO records Vol. 47 Page(s) 17873)

The Sec. cor., perpetuated and recorded by Wenderoth in 1953, monumented with an iron pipe, 3/4" dia., firmly set, projecting 7" above ground, from which the remains of a bearing tree mkd. by Thiel:
A Fir snag 36" dia., bears N.19½°E., 30 lks. dist., with scribe marks T32S R5W S24 visible on open blaze. (Rec. N.16°E.)
and the remains of bearing trees mkd. by Wenderoth
(Cont. Next Page)

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 20" dia., bears S.70¼°E., 14 lks. dist., with healed blaze.

A root hole bears S.18½°W., 64 lks. dist., alongside of which is a down Fir, 16" dia., with healed blaze.

A Fir 21" dia., bears N.74°W., 84½ lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, directly over iron pipe, with brass cap marked

T 32 S R 5 W
S 23 | S 24
S 26 | S 25
1983

from which new bearing trees

A Fir 12" dia., bears N.31°E., 39½ lks. dist., mkd. T32S R5W S24 BT.

A Fir 6" dia., bears S.63°W., 85 lks. dist., mkd. T32S R5W S26 BT.

Fd. OK by Nygren, Aug. 1998 - M130-34

Fd. BC & 4 BTs, set 6' steel post 2' north, D.Edwards 4/2008
M155-51